HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	**Little Rock, AR:**	833-424-8944
Baltimore, MD:	888-601-7500	**Portland, ME:**	800-325-4253
Concord, NC:	800-438-2250	**Raleigh, NC**	833-418-9777
Delmar, DE:	866-486-1400	**Scranton, PA:**	800-569-1400
Des Moines, IA:	888-673-5011	**Springfield, MA:**	800-854-5306
Elkton, MD:	800-544-7127	**Voorhees, NJ:**	800-232-6535
Jacksonville, FL:	800-828-3055	**Walpole, MA:**	800-854-5310

haletrailer.com • follow us online **@haletrailer**

800-232-6535 *FINANCING AVAILABLE

ABS

A042348-A042350
VIN: S040941-S040943

Lenght	38' / 11.56m	**Volume capacity**	37 V³(yd³) / 28 M³
Width	102" / 2,59m.	**Side loading height**	122" / 3,10m
Highest point	133" / 3,38m	**Axle spread**	54" - 54"
King pin set back	16"	**Total weight**	8 500 kg

Bolted Subframe	STRENX, high tensile strength steel 100 000 PSI; Fully hot dip galvanized
Main Beams	STRENX, high tensile strength steel 100 000 PSI;
Tub side walls	HARDOX AR500 TUF 3MM
Cross-members	Bolted I BEAM, help to avoid weld cracks;
Coupling plate	5/16 STRENX (100,000 PSI), with convex shape at king pin;
Tailgate	Aluminum made, using 2 pneumatic cylinders
Safety lock	pneumatic cylinders
Outside walls	Aluminum 14 gauge (0.064") unpolished,
Paint Sandblast	cleaned + epoxy primer, + polyurethane paint, black or customer color;
Self-Steer Axle	N/A
Primary axles	INTRAAX HENDRICKSON ZMD F24, capacity 25 000 Lbs.
Suspension SSA	N/A
Suspension primary	INTRAAX HENDRICKSON, capacity of 25,000 lbs;
Hub&drums	WEBB, unimount 10 holes, long stud;
Brake friction mat	16.5 X 7 Q-brake;
Brake cylinder	booster Type 30/30, 2.5" of stroke;
Slack adjustor	HALDEX, 5.5";
Air tank	Aluminium air tank
Bearings	Inner bearing and outer bearing # 518445;
Wheels seals	HENDRICKSON S-27268-HP
Nuts for Hub&drums	PRECISION320®
Hubcaps	HXL3 Ventless, Bolt-on
Tires	PLANT CHOICE 11R22.5,16 plys,
Aluminum rims	ALUMINUM WHEELS
ABS brake system	BENDIX, 2S/1M;
Lights	GROTE, LED, side signals, on Transport Canada regulations;
Landing gear	HOLLAND MARK "V", two speeds, driver side installation.

Standard equipement included

Axles Fenders	Plastic fenders
Front Fenders	Aluminum, designed to protect frame at tractor drive tires location;
Tailgate (Control)	Opening operation ready to connect to tractor or manually operating;
Tailgate (Indicator)	Open tailgate indicator on both sides;
Tailgate (Speed)	Slowing devices on tailgate opening and safety locks closing operations;
Inspection windows	Both sides on rear, protected by a safety cover;
Ladder on side	included
Front door	Optional
Strobes lights	Located on both sides at rear, ready to connect on tractor by customer;
Drop valve	Located in the air box, allow to drop all suspension for long term parking;
Air gauge	Located on driver side at front, show the air pressure in suspension air bags;
Hydraulic gauges	Located on front pressure line , show PSI;
High pressure valve	Optional
Flow control valve	Optional
Check valve	Set on the return line;
Shaft rotation indicator	indicator Both sides at front, shows if conveyor motion is started;
Wet kit hyd	connector's Wing nut type, one male and one female, 1 '' diameter;
Lift axle & steer axle	Under beam lift connected to an electric valve wired at the front
Tarp system	See possible options

Conveyor

Planetary reducer	(2) PLANETARY with (2) hydraulic orbital motor;
Normal range	PSI Stall torque is 1 900 PSI decreasing while unoading;
Oil displacement	GPM Tractor must supply from 25 to 35 GPM. (standard dump pump 3 lines);
Conveyor belt	2 ply's belt with cover of 3/16 and 1/16, asphalt resistant;
Conveyor chains	2 chains pintle type, no rollers to seize but must be oiled at all time;
Seals	ABS unique design, bolt on for easy adjustment;
Conv. cross member	Steel tubing 1 X 2 with skates on each end sliding on low friction material;
Chains oiling system	ABS unique design system, located on rear side, using flow control valves.

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.