HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

DORSEY ESTABLISHED 1911

A042352-A042353
VIN: 55194-55195

Base Model #: DF48 x 102 RAS 22.5
Serial #: 55194 - 55195

components description
CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - Base Weight 12,200#
TOP DECK-LGTH/HGT 10' Length = 59" Height
LOWER DECK-LGTH/HGT 38' Length = Front 41", Center 42" Rear 40" Heights
OVERALL WIDTH 8' 6"
KING PIN SETTING 18" - Squared Front
UPPER COUPLER PLATE 3/8" - Powder Coated Upper Coupler Assembly
UPPER COUPLER HEIGHT 48"
BULKHEAD None
MAIN FRAME 26" PreCamb Beam-130K Tru-Strength Flanges - Limited Lifetime Warranty
SIDE RAILS 6" - 6.5# Per Foot
TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE None
FLOOR DECKING 1-1/8" Apitong
WINCH TRACK Steel Slide Entire Length of ** Road ** Side Only
WINCHES 12
STRAPS None
LANDING GEAR Two Speed - Jost A500
SUSPENSIONS Air Ride-Hendrickson Intraax - 23K 2 Axle - RAS
SUSPENSION LOCATION Rear Axle Slider
AXLES (2) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires(HXL5 Grease)
AXLE SPACING RAS - 2 Position 49" and 10'-2"
LIFT AXLE None
DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)
SCALES None
PARKING BRAKES All Axles
ABS SYSTEM Wabco ABS System 2S/1M
DUST SHIELDS None
WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES 255/70R 22.5 - Firestone 560
TIRE INFLATION SYSTEM None
ANTI-SAIL MUD FLAPS Behind Rear Axle On Slider
STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear
PIPE SPOOLS Double
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
DOCK BUMPERS Rubber Inboard
CARGO TIE DOWN None
CONTAINER TWIST LOCKS NONE
TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear
TOOLBOX TYPE None
TOOLBOX LOCATION None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS None
PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted
DECAL PACKAGE Standard Dorsey Logo Kit
CUSTOM 1. Grote Document Holder Landing Gear R/S

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.