

2017 33'SL Tridem

Container Chassis / 42373-42378

1. Function

Carries one (1) 20' ISO container.

Meets all TOFC, AAR, DOT, FMVSS, ISO, ANSI, SAE and TTMA specifications

2. General

Overall Length:	41'	(Excluded rear bumper)
Overall Width:	96"	
Fifth Wheel Height:	48-5/8"±1"	
Rear Deck Height:	53-1/4"±1"	
Kingpin Location:	15"	(From front face of front end)
Axle Spread:	54-1/2"	
Tridem Location:	80-1/8"	(From rear end to tridem center)
Tare Weight:	11,200 Lbs (±2%)	
Gross Vehicle Weight Rating:	78,400 Lbs	

3. Steel Structure & Components

Material:	High strength GR80 steel for main beam, GR50 steel for other parts.
Painting:	E-coat primer (minimum 20µm) and Powder coating topcoat (minimum 60µm). 7 years warranty. Color Black.
Main Beam:	14" deep x 5-13/16" wide fabricated H-beam consisting of 1/2" flange and 5/16" web.
Slider beam:	10" deep x 5-13/16" wide fabricated H-beam consisting of 1/2" flange and 5/16" web.
Crossmember:	3/16" & 1/4" thick Fabricated channel with integral gussets on top.
Upper Coupler:	5/16" thick w/ 2" dia. drain holes, reinforced by 1/4" thick channel type king pin support. Holland 2" AAR certificated kingpin.
Bolster:	8" wide x 3/8" thick top plate with 7-1/4" wide x 7-1/4" deep x 5/16" thick "U" channel.
Rear Bumper:	4" x 4" square type step bar supported by 'C' type posts
Twist Locks:	Schulz F77ANS or Buffers equivalent.
Landing Gear:	Holland 55,000 lbs capacity, 2-speed 19" travel, low profile sand shoe. Roadside crank handle.
Suspension:	Hutch mechanism tridem suspension w/ spring 324-01.
Axles:	Holland 5" round axles with 22,500 lb capacity, 71-1/2" track, Haldex 28 spline, 5.5" automatic slack adjusters. 16-1/2" x 7" Q Brake.
Lubricant:	Stemco seal, Mobilith SHC 007 synthetic grease lubricant with metal hubcap.
Hub & Drum:	10 stud hub piloted hubs with outboard mounting cast steel drum.
Rims:	Jingu 22.5 x 8.25 hub-piloted wheels.
Tires:	Westlake 295/75R22.5 tubeless type, 14 ply, CR915.
Brake System:	WABCO 4S/2M ABS brake system, spring brake priority. Phillips 12-008/12-006 gladhand and Haldex type 3030 2.5" stroke break chamber.
Electrical:	Truck-Lite 12 volt LED lighting system with Phillips modular wiring harness. The theftproof design used for 4" LED lighting.
MISC:	CIMC standard marking, Conspicuity tape, Document holder, 18" X24" Black rubber mud flap with CIE logo.
OPTIONS:	PSI Tire inflation system, with LED indicator lamp. Without Thermo-Alert.

DISCLAIMER

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS. PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL. EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.