HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	**Little Rock, AR:**	833-424-8944
Baltimore, MD:	888-601-7500	**Portland, ME:**	800-325-4253
Concord, NC:	800-438-2250	**Raleigh, NC**	833-418-9777
Delmar, DE:	866-486-1400	**Scranton, PA:**	800-569-1400
Des Moines, IA:	888-673-5011	**Springfield, MA:**	800-854-5306
Elkton, MD:	800-544-7127	**Voorhees, NJ:**	800-232-6535
Jacksonville, FL:	800-828-3055	**Walpole, MA:**	800-854-5310

haletrailer.com • follow us online **@haletrailer**

800-232-6535 *FINANCING AVAILABLE

Travis BODY & TRAILER, INC.

A042424-A042425
VIN: S041009-S041010

BOTTOM DUMP - SHORT FORM

STANDARD SPECIFICATIONS: TRAVIS ALUMINUM BOTTOM DUMP

ALL ALUMINUM CONSTRUCTION
Extruded tubular longitudinal lower rails
Extruded top rail
Extruded horizontal rail
Extruded I-beam sub-frame
Extruded aluminum drop legs (mounted on gates)
.160" thick aluminum hopper sides and inner slope plates
.250" thick aluminum chute ends and sides
.250" thick aluminum gate inner sheet
.125" thick aluminum outer shed plates
Smooth aluminum front & rear fenders
12 degree side wall slope
99" outside body width / 91" inside at top rail

GATE
.250" thick 5454 H34 aluminum chute
106" X 50" opening, 14" ground clearance
Infinitely adjustable electronic control valve with dryer & oiler (jogging valve)
(2) 8" diameter, 26" stroke, composite lightweight air cylinders with positive stops
Aluminum air reservoirs

CHASSIS / UNDERBODY RELATED
Rocking upper coupler, 2" diameter Steel pin, 8 degree oscillation
5/16" T-1 steel coupler plate
Hutchens CH9700 single leaf, 4-spring suspension, bolt-on
5" round axles (2), 5/8" wall, common inner/outer bearings
Automatic slack adjusters
16-1/2" X 7" air actuated brakes
Wabco ABS - 4S/2M
Cast steel hubs - hub piloted
Outboard drums
Radial tires (choice of size)
ALUMINUM hub-piloted

OTHER STANDARD FEATURES
Ladder on front shedder plate with safety rail and steps
HMW plastic, 1/2" thick, windrow deflector
D.O.T. conspicuity tape (3M)
Silver enamel paint on steel parts
Anti-spray, anti-sail rear mud flaps
Truck Lite sealed light system
Removable drop legs

All Travis trailers conform to Federal Motor Vehicle safety standards in effect at time of production. Because of continuous improvements, the above specifications are subject to change without notice.

MODEL **Aero Tandem**	LENGTH	KP to REAR AXLE	BASE WEIGHT	CUBIC YARDS CAPACITY
Aero 40/24	**40' 2"**	**36' 7"**	**10,500**	**24.00**

CHANGES FROM STANDARD: For TYPE of change: D = Delete Standard Specification, A = Alter Standard Specification, O = Add Optional Equipment

No.	TYPE	DESCRIPTION	WEIGHT +/-	YDS +/-
		69" Side height with standard 10' hopper/gate	100	**4**
		HT300 Air Ride Tandem No Lift		
		Push Bumper	190	
		Roll Rite Electric Flip Tarp Mesh (Front to Back)		
		Safety Pin Bars		
		Estimated Cubic Capacity is 28 yards		
		10,500 lbs. + or - 3% — **We don't grease pack bearings**		

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.