HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

DORSEY ESTABLISHED 1911

A042426-A042431
VIN: 55432-55437

Serial #: 55432 - 55437

components description
CAPACITY Heavy Duty Package - 120,000 lbs. GVWR (110K Eq. Dist. & 90,000 in 10' Span)
OVERALL LENGTH 48'
UPPER DECK LENGTH 12'

* * * Minimum Pitch of 2-3/4" * * *
LOWER DECK LENGTH 36' (Deck Height-42")
OVERALL WIDTH 8' 6"
KING PIN SETTING 18"
UPPER COUPLER PLATE 5/16"
UPPER COUPLER HEIGHT * * 50" * *
BULKHEAD None
MAINFRAME 26" Fabricated - PreCambered I-Beams - Heavy Duty
* * Main Beams 1/2" X 6" Top Flange, 3/4" x 6" Bottom, 1/4" Webs Throughout, Lower Deck, 1/4 Rear Section, 1/4" Web in Neck. * *
* * Transition Plate * *
* * 1/4" Diamond Plate Over Wheels. * *
* * * 1/4" Diagonal Bracing, Main Beam to Outer Rail. * * *
* * * * Rear of Trailer Prep for 4th Flip Axle. * * * *
SIDE RAILS 8" Heavy Duty
FLOOR SILLS 6" I-Beam 12/12/12 O.C. HD Pkg. Drop Frame
* * Approx. 6 Aux. Crossmembers over Suspension at Middle of Trailer, and in Gooseneck. * *
* * Install Sub Sills in High Stress Areas. * *
FLOOR DECKING * * 1-1/2" Apitong * *
WINCH TRACK Steel Slide Entire Length of Drivers Side
WINCHES 12
STRAPS None
LANDING GEAR Two Speed
SUSPENSIONS (Hendrickson)- 30K Suspension W/ (30K) Lift Rear Axle
9" Ride Height.
LIFT AXLE Lift Rear Axle
DUMP VALVE Dump Valve in Box Includes: Manual Override, Liquid Filled Gauges and Lift Axles
** All Air Control valve in Box.**
SCALES None
AXLES (3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride(Parallel Spindle)
Parallel Spindle.
23K Brake Linings.
AXLE SPACING 61" Wide Spread
PARKING BRAKES 3 Axle
DUST SHEILDS None
WHEELS Disc - Hub Piloted - Steel Inside and Polished Aluminum Outer
* * * * Steel Inside, Polished Outside w/ Wheel Pads Between Wheels * * * *
TIRES 275/70R 22.5 - 42" Loaded Deck Height
Double Coin.

ANTI-SAIL MUD FLAPS Rear Frame
STAKE POCKETS 4" Deep - 24" O.C. - Sides Only
RUB BAND STEEL 3/8" X 3"
Shop Print - Quote: 90395 Page 2 of 2
PIPE SPOOLS Double
DOCK BUMPERS None
* * * * Heavy Duty Rear Skirt and Rear End Material * * * *
* * * Aluminum Sheet on Outside Rear to Cover 3 Light Stop/Tail/Turn * * *
DOVETAIL None
LOADING RAMPS None
TIRE CARRIERS None
CARGO TIE DOWN None
TOOLBOXES None
TOOLBOX TYPE None
LIGHTS Sealed Wiring Harness w/ LED Pkg
Use Flange Mounted Anti-Theft S/T/T On Rear Skirt, (Due To Skirt Thickness).
5 Pair Of Belly Lights On Toggle Switch.
PAINT Black - Sherwin Williams Epoxy Primer and Acrylic Polyurethane - Shot Blasted
CUSTOM 1. Strobe Kit- 3-3-3 Toggle Switch - D/S - Rear Trailer
CUSTOM 2. Grote Document Holder Landing Gear R/S
CUSTOM 3. Heavy Duty Decals
Reference #: 48411

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.