

HALE

T R A I L E R

B R A K E & W H E E L

Hale Trailer Brake & Wheel
062321 - 062325



- Style** **CTSSF-45' x 12'4" HIGH x 8'6" WIDE (18" BEVELED CORNERS)**
(12"10" AT TOP OF ARCH)
- Tires** **11:00 X 24.5 GENERAL RA (16 PLY) RADIAL TIRES**
- Wheels** **24.5 X 8.25 STEEL- UNIMOUNT**
- C/M** **ALUMINUM ON 12" CENTERS- 8" CENTERS OVER SUSPENSION**
- Post** **14.5" CENTER**
- Skin** **.063 PREPAINTED WHITE- NORTH SKIN DESIGN- "ECK" SPRAYED BETWEEN STEEL ALUMINUM- FRONT NOSE SKINS PANELS TO BE PREPAINTED BLACK LAST TWO (2) SKINS EACH SIDE WILL BE FURNISHED BY HALE TRAILER AND WILL BE .125 THICK**
- Tarp** **SHUR-LOCK ROLL TARP- BLACK IN COLOR- REAR CRANK- TELESCOPING POLE W/ FLEX HANDLE- CUT FLUSH AT REAR- 6" TARP CAPS- NO TARP BOWS- HANDLE HOLDERS ON BOTH SIDES- ADD "SPACER" TO HANDLE HOLDERS**
- Axles** **25,000# 77" TRACK- HP SPINDLES - (SAME BEARINGS)**
- Susp.** **RIDEWELL RAR266 SUSPENSION WITH SLIDER**
- Door** **SIDE HINGED- "POLYMER CORE" FREIGHT DOORS- STAINLESS STEEL HARDWARE- 6" ARCHED DOORS & HEADER- OFF SET HINGES- SKINNED WITH FLAT STAINLESS STEEL ON THE OUTSIDE- MILL FINISH ON THE INSIDE**
- ABS** **2 S - 1 M**
- Floor** **KEITH 7/32" W/ WEAR STRIPS- 3.5" DRIVE- HALE TO FURINSH- KNL TO INSTALL- STAINLESS STELL LINES**
- King Pin** **- 37" KP SETTING - 49" KP HEIGHT - 36" LA LOCATION- NEEDS TO BE 18" OF RADIUS AROUND KING PIN**

**Lights [X]] LED- BACK UP LIGHTS MOUNTED IN BUMPER- WORK LIGHTS INSIDE FRONT-
- WIRED TO FRONT IN WATERPROOF SWITCH**

Ladders [X] ALUMINUM FRONT LADDER ONLY- STEEL SAFTEY LOOPS

PAINT [X] STEEL COMPONENTS PRIMED AND PAINTED WHITE

[X] ENCLOSED " REFUSE STYLE" TOP RAIL

[X] FIVE (5) ARCHED CROSS TIES- BOLTED TYPE

[X] ALUMINUM BOTTOM RAIL

[X] STAINLESS STEEL HEADBOARD AND REAR DOOR FRAMES

[X] STAINLESS STEEL HYDRAULIC LINES

**[X] AIR & LIGHT CONNECTIONS MOUNTED ON DRIVERS SIDE – HYDRAULIC CONNECTION
MOUNTED ON CURB SIDE**

[X]AIR GAUGE RECESSED IN BEVELLED CORNER- DRIVERS SIDE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.