



Hale Trailer Brake & Wheel
062329 - 062330

- Style** [X] CTSSF-45' X 12'4" HIGH X 8'6" WIDE (18" BEVELED CORNERS)
(12'10" AT TOP OF ARCH)
- Tires** [X] 11:00 X 24.5 GENERAL RA (16 PLY) RADIAL TIRES
- Wheels** [X] 24.5 X 8.25 - STEEL, UNIMOUNT
- C/M** [X] ALUMINUM ON 12" CENTERS- 8" CENTERS OVER SUSPENSION
- Post** [X] 14.5" CENTERS
- Skin** [X] .063 PREPAINTED BLACK- NORTH SKIN DESIGN- "ECK" SPRAYED BETWEEN STEEL ALUMINUM - FRONT NOSE SKINS PANELS TO BE PREPAINTED BLACK- LAST TWO (2) SKINS EACH SIDE WILL BE FURNISHED BY HALE TRAILER AND WILL BE .125" THICK
- Tarp** [X] SHUR-LOK ROLL OVER TARP- BLACK IN COLOR- REAR CRANK- TELESCOPING POLE W/ FLEX HANDLE- CUT FLUSH AT REAR- 6" TARP CAPS- NO TARP BOWS- HANDLE HOLDERS ON BOTH SIDES- ADD "SPACER" TO HANDLE HOLDERS
- Axles** [X] 25,000" - 77" TRACK- HP SPINDLES- (SAME BEARINGS)
- Susp.** [X] RIDEWELL RAR266 SUSPENSION WITH SLIDER
- Door** [X] SIDE HINGED- "POYMER CORE" FREIGHT DOORS- STAINLESS STEEL HARDWARE- 6" ARCHED DOORS & HEADER- OFF SET HINGES- SKINNED WITH FLAT STAINLESS STEEL ON THE OUTSIDE- MILL FINISH ON THE INSIDE
- ABS** [X] 2 S - 1 M
- Floor** [X] HALLCO FLOOR 3/16" W/ WEAR STRIPS- 3.5" DRIVE- HALE TO FURNISH- KNL TO INSTALL- STAINLESS STEEL LINES
- King Pin** [X] - 37" KP SETTING- 49" KP HEIGHT - 36" LA LOCATION- NEEDS TO BE 18" OF RADIUS AROUND KING PIN
- Lights** [X] LED- BACK UP LIGHTS MOUNTED IN BUMPER- WORK LIGHTS INISDE FRONT- WIRED TO FRONT IN WATERPROOF SWITCH

Ladders [X] ALUMINUM FRONT LADDER ONLY- STEEL SAFTEY LOOPS

PAINT [X] STEEL COMPONENTS PRIMED AND PAINTED BLACK

[X] ENCLOSED : REFUSE STYLE" TOP RAIL

[X] FIVE (5) ARCHED CROSS TIES – BOLTED TYPE

[X] ALUMINUM BOTTOM RAIL

[X] STAINLESS STEEL HEADBOARD AND REAR FRAMES

[X] STAINLESS STEEL HYDRAULIC LINES

[X] AIR & LIGHT CONNECTIONS MOUNTED ON DRIVERS SIDE- HYDRAULIC CONNECTION MOUNTED ON CURB SIDE

[X] AIR GAUGE RECESSED IN BEVELLED CORNER- DRIVERS SIDE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.