



Hale Trailer Brake & Wheel

062800-062801

PEERLESS ROADRUNNER TRAILER

CHIP TRANSPORT SEMI: Dual Axle, 45' Length, 15.3 Unit Capacity, Exterior Post Construction

STANDARD SPECIFICATIONS: CTS-45

Design:	Box design, reinforced for dumper pick up, end dump design
Construction:	Skin stressed .063 natural aluminum with aluminum exterior posts (21.5" centers)
Capacity:	14.2 units (104.91 cu yd)
Dimensions:	45' length, 8' 0" width, 13' 6" height, 37" king pin location, 36" rear axle location
Tires:	Eight (8) 11:00 X24.5 Double Coin RR150 radial tires
Wheels:	Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount
Axles:	22,500# cap. , <u>77 1/2" track</u> , 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks
Brakes:	16 1/2" x 7" air, Q Plus with CM-212 lining, type 3030 air chambers, DOT relay emergency system, dump valve
A.B.S.:	2 sensor - 1 module
Suspension:	Four spring three leaf tandem (Hutch H9700T)
Landing Gear:	Two speed, crank on driver's side (Holland Atlas 55)
King Pin:	Standard SAE, heat treated, 37" setting, 51" height
Cross Sills:	4" Jr. I-beams located on 22" centers
Decking:	.063 aluminum
Top:	Flat design, open top, single center tie
Top Cover:	Shur-lok roll over tarp – mesh material – crank at rear – handle holders on both sides – flat front and rear tarp caps
Tarp Bows:	Optional



Rear Door: Full size, hinged at top, skinned with solid aluminum or expanded metal

Dump Stand: Two blades at rear for standard Peerless backstop

Ladders: One located at front, one located at rear

Rope Hooks: Optional

Tire Carrier: None as standard

Mud Flaps: Legal rubber

Wiring: Unitized wiring system, 12 volt

Lights: Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights

Reflectors: Legal DOT

Paint: Aluminum natural, steel components primed and painted black

Weight: Approximately 10,750#

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.