Hale Trailer Brake & Wheel
066446 - 066475

ALUMINUM "BST II" PLATFORM TRAILER

LENGTH:	48' - 24" BEAM
WIDTH:	102"
NOSE:	SQUARE +
	EXTRA 6-WAY CONNECTOR (1) (4)
KING PIN SETTING:	30" - 5/16" PLATE - NO ACCESS HOLES
FLOOR:	KNURLED ALUMINUM
	3 NAILERS
	INTEGRATED SIDE RAIL
XMEMBER SPACING:	16" SPACING
COIL PACKAGE:	YES - w / 8 PCS BAR INSERTS
SPOOLS:	DOUBLE
POCKETS:	HD FRONT TO ACCEPT AERO BH SEE DWG
ROPE HOOKS:	NONE
TIE DOWNS:	Two Tie Down Storage Pipes D/S @ LG
MARKER LIGHTS:	LED - 7 EACH SIDE
MID TURN SIGNAL:	MMTS BELOW RAIL - Inboard & Angled
LIGHT PANEL:	LED - STD 9 LIGHTS OOO ooo OOO
	1/2 STEPS ON REAR
	FULL WIDTH BUMPER
BULKHEAD:	NONE
TYPE:	
HEIGHT:	
RETURNS:	
MAT'L:	
ACCENT TAPE:	BLACK
PAINT:	BLACK
	SOFT COAT BLACK ON SUSPENSION
WINCH TRACK:	INTEGRATED BOTH SIDES
LOCATION:	
WINCHES:	12 - STEEL SLIDING - D/S
WINCH CLIPS:	12 - ALUM SLIDING - P/S
STRAPS:	NONE

SUSPENSION:	AAT25K / E2-1 REAR AXLE SLIDER **(2)**
LOWERING KIT:	AUTOMATIC
AXLE TO AXLE:	56" & 125" **(2)**
AXLE TO REAR:	46"
LIFT / AXLE:	N/A
SPACING:	
F.W. HEIGHT:	**49"**
CONTROLS:	
AXLES:	TP SPINDLES
	23,000 GAWR RATED
AUTO SLACKS:	MERITOR
BRAKES:	16-1/2" x 7"
ABS SYSTEM:	4S / 2M (SENSOR ALL)
HUBS:	10 STUD LWSTEEL / LW DRUMS
	LIGHT WEIGHT BRAKE DRUMS
WHEELS:	8.25 x 22.5 ALUMINUM
	4 CLEAN BUFF / 4 POLISHED
TIRES:	11R 22.5 R196 14 PLY BS
LANDING GEAR:	2 SPEED JOST ALUMILGHT AX150 (3)
	FORWARD BRACING - D/S CRANK
TIRE CARRIER:	BRACKETS ONLY - P/S ACCESS MID TRAILER
TOOLBOX: QTY:	NONE
SIZE:	
LOCATION:	
MAT'L:	
MUDFLAPS:	STD
TYPE:	SILVER PLASTIC
LOCATION:	ON REAR OF SLIDER BOX + 3/16" ALUM
	ON TOP OF SLIDER FLAP BENT TOWARD
	TIRE.

REMARKS:

(1) EXTRA 6-WAY WIRED TO JUNCTION BOX D/S INSIDE FRAME IN FRONT OF MOST FORWARD AXLE
(2) 2 POSITION REAR AXLE SLIDER - SLIDER BOX INSIDE MAIN FRAME RAILS
SLIDER BOX & REAR HANGERS TO BE BLACK SOFTCOAT - GALVANIZED HANGERS FRONT AXLE ONLY
(3) TRUCKLITE REGISTRATION HOLDER D/S @ LG
(4) WIRING BACK 3" FROM INSIDE NOSE

WEIGHT: 9935

DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.