



Hale Trailer Brake & Wheel
067500 - 067508



TK80ACS-34 Steel/Aluminum Combo Step Deck Trailer

13813-ACS-34

Overall Width: 102"

Fully Loaded Deck Height: 34"

Loaded Ground Clearance: 9"

Capacity:

2-axle: 80k Distributed

3-axle: 85k Distributed

Upper Deck Crossmembers 18" O.C.

Main Deck Crossmembers 12" O.C.

Aluminum Rub Rail w/ Chain Spools

Stake Pockets (24" O.C.)

Full-Length Hook Track

Anti-corrosion Barrier Between Aluminum & Steel

| Item # | Category | Description | Weight (lbs) | Qty |
|--------|------------------------|--|--------------|-----|
| 13813 | Open Deck | TK80ACS-34 Steel/Aluminum Combo Step Deck Trailer | 9,575 | |
| 13818 | Overall Length | 52'-10" Overall Length | 509 | |
| 13819 | Aluminum Content | Standard Aluminum Content | | |
| 13821 | Fifth Wheel / King Pin | 14" Kingpin Setting (82"/88"/94" Swing Clearance w/ 10'/10'-6"/11' Upper Deck) | | |
| 13824 | Fifth Wheel / King Pin | 48 - 50" 5th-wheel Height | | |
| 13827 | Upper Deck | 10' Upper Deck Length | | |
| 13830 | Main Deck | 60k in 10' Concentrated Load Rating | | |
| 13832 | Decking | Aluminum Decking w/ Flush Apitong Nailers | | |
| 13843 | Tie Downs | Winch Track Stops: Removeable | | |
| 13835 | Tie Downs | No Sliding D-Rings on Upper Deck | | |
| 13837 | Tie Downs | No Sliding Winches on Upper Deck | | |
| 13839 | Tie Downs | No Sliding D-Rings on Main Deck | | |
| 13842 | Tie Downs | Sliding Winches on Main Deck (each) | 96 | 12 |
| 13845 | Tie Downs | No J-hooks | | |
| 13847 | Tie Downs | No Stake Pockets on Rear | | |
| 13850 | Suspensions | Tandem Axle: (1) 23k Air Ride w/ (1) 23k Air Ride Rear Slider | 271 | |

| | | | | |
|-------|-----------------------------------|--|------|---|
| 13956 | Suspensions | Suspension Set Ahead 42" w/ Underride Guard (California Legal for 52'-10" OAL, 14" KP, & 49"/121" Slider Spacing - Not Canadian Overhang Legal) | 23 | |
| 13858 | Suspensions | 49" Closed / 121" Open (slider only) | (68) | |
| 13861 | Axles | Standard Axle | | |
| 13867 | Brakes / Air | 2S1M / 2S2M Anti-Lock Brake System | | |
| 13869 | Brakes / Air | 20k Drum Brakes (per axle) | | |
| 13871 | Hub / Drum | Steel Hub-Piloted - Cast Drum (per axle) | | |
| 08182 | Wheel Finish | 6.75 x 17.5 8-hole steel disc wheel (inside) | | |
| 08194 | Wheel Finish | 6.75 x 17.5 8-hole polished (AIP) aluminum wheel (outside) (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel | (96) | 4 |
| 10058 | Spare Wheel | No spare wheel | | |
| 07907 | Tire Size | 235/75R17.5 - 18 ply HTL2 (tire only) (per tire) | | |
| 10059 | Spare Tires | No spare tire | | |
| 13874 | Spare Tire Carrier | No Spare Tire Carrier | | |
| 13876 | Flaps, Mud Guards & Fenders | Mudflaps: Rear Axle Only (standard TK) | | |
| 13878 | Landing Gear | Standard Two-Speed (crank road side) | | |
| 13879 | Toolbox | No Toolbox | | |
| 13882 | Bumper | No Non-Certified Bumper | | |
| 13884 | Flagholders | Standard Flagholders (3 per side) | | |
| 13885 | Document Holder | Document Holder: 4-1/2" Round | | |
| 13886 | Lights / Electrical | LED Lights - DOT Required w/ Midturn & 3rd Taillight (XOX) | | |
| 08024 | Paint | Black S7203 with white decals (735-432-039) | | |

13813-Additional Options

| Item # | Category | Description | Weight (lbs) | Qty |
|----------|-------------------|---|-----------------|-----|
| 09999-01 | Custom Options | Trl equipped with Hendrickson HT250 ILO std | | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.