Hale Trailer Brake & Wheel
071345-071347

EAST *GENESIS* UNLOADER TRAILER

OPEN TOP [X] CLOSED TOP [ ]

"GENESIS"

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM + LIFT (5)
LENGTH (FEET)	48	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	54" (3)
FRONT 0.150		S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE 0.150		GATESEAL	YES	PIN SETTING	36" W/ 3/8" PLATE
REAR 0.150		GATE LADDER	Commercial - Center	SUSPENSION	AAT30K / E2-1 (6)(7)(14)
POLISHED SIDES	NO	TARP HOOKS	NONE	SPRINGS	AIR (8) (9)
ROOF	NONE	WINDERS	ONE - D/S	AXLES	TP SPINDLES
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" (1) MAN DOOR	GATE CONTROL	MECHANICAL	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO (13)	ABS	2S / 1M
TARP	NONE		TUBE TYPE	HUBS	10 S STL / CAST-PIL
CATWALK	YES - FULL WIDTH				EAST ELITE
B.H. LADDER	Commercial - D/S	COMPACTOR:		WHEELS	8.25" x 24.5"
CROSSMEMBER	"I" BEAM - 12" C/L	SIDE LATCH	N/A		6 STEEL / 6 POL (10)
FLOOR MAKE	KEITH (2) (3) (4)	CENTER LATCH		TIRES	11R 24.5 GRABBER
FLOOR MAT'L	2299	PIN DIA.			OA 16 PLY (11)
WEARPADS	CWS			DOLLIES	2 SPEED JOST A451
TAPE COLOR	BLACK IN TOP RAIL	HYDRAULICS:		LOCATION	D/S CRANK
LIGHT PANEL	LED - IN GATE	HOSES	TWO-4000 PSI (12)	BUMPER	EAST UNDERRIDE
MARKER LIGHTS	LED -8 PR (14)	LENGTH	108"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES - LED	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	YES	HP	1" FEMALE	PAINT	BLACK
HOSE HANGER	ON BULKHEAD	LP	1"		
TIRE CARRIER	NONE				

REF # E11935 70934

WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.

1. MANDOOR IN CENTER OF BULKHEAD
2. DRIVE UNIT TO HAVE 3-1/2" CYCLINDERS -- ALUMINUM DRIVE AND STAINLESS TUBING
3. "T"-BLOCKS AT REAR. DRIVE UNIT FLOOR OPENING MOVED FORWARD FOR TRIDEM
   MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES - NOTE 54" REAR AXLE SETTING
4. EXTEND SUB FRAME AS NEEDED TO ACCOMMODATE AXLE SPACING AND HAVE ALL AXLES MISS DRIVE UNIT
5. AAT30K MAIN TANDEM w / AAL30K/R1 LIFT AXLE BEHIND TANDEM. (LIFT AXLE TO HAVE SWITCH IN BOX AND ELECTRIC CAB CONTROL OPERATIONS)
6. ALL CONTROLS TO BE IN WEATHER TIGHT BOX IN FRONT OF FIRST AXLE, AND WIRED FOR CAB CONTROL THRU AUX 7-WAY ISO PLUG (17)
7. GALVANIZED SUSPENSION HANGERS
8. USE ALUMINUM AIR TANKS
9. ALL 3 AXLES TO EQUALIZE FROM REAR TO FRONT AAL30K/E-3AAT30K/E-2-1
10. STEEL INSIDE / ALUM OUTSIDE. USE WHEEL GUARD INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
11. HENDRICKSON TIRE MAAX PRO ALL AXLES
12. HYDRAULIC HOSES TO BE LOCATED ON PASSENGER SIDE -REFERENCE VIN# 68615.
13. REAR CROSSPIPE MOVE FORWARD 1' FROM STANDARD PLACEMENT.
14. **LED - 8 PR 30385Y/R MARKER LIGHTS BOTTOM ONLY W/ PROTECTORS.** **CHANGE 1**

OVERALL HEIGHT (FT) 13.25 **EMPTY WEIGHT (#)** 20,701 **CUBIC YARDS** 125

14. RIGHT WEIGH OIL FILLED GAUGE IN LBS. MOUNTED IN BULKHEAD ON D/S RADIUS FOR DRIVER VISIBILITY- REFERENCE PIC BELOW
15. LIFT AXLE TO HAVE BRAKE RELEASE VALVE
16. DO NOT INSTALL CROSSOVER KIT
17. ELECTRICAL LOCATION -CENTER-REFERENCE 68615





DISCLAIMER
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.