



Hale Trailer Brake & Wheel

071352-071354



GENESIS FRAMELESS DUMP

BODY SPECIFICATIONS

Length	40'	Body	* FRONT TARP CAP W/ 12" RISE
Width	102" INBOARD	Tarp	NONE
Side Height	72" SOLID	Bow Holders	NONE
Top Rail	9" DUMP	Tarp Bows	NONE
Side Matl-front	20' - .100" WALL	Tarp Basket	NONE
-middle	10' - .140" WALL	Tarp Hooks	NONE
-rear	10' - .180" WALL	Bulkhead Mat'l	3/16"
Side Options	NONE	Bulkhead	D/S-MANDOOK
Floor Mat'l	1/4" (3/8" LAST 10')	Options	
Crsnbr Spacing	12" (10" CROSSMEMBER SPACING OVER SUSPENSION)	Body Fenders	SQUARE OFF
Floor Options	NONE	Ladders (Out)	D/S-LAST PANEL
Tailgate Control	AIR FRAME+ ELEC CC (1)(9)(10)	Inside	NONE
Body Pkg	NONE	Shovel Hgr	NONE
Options		Light Panel	FULL - LED;X=LED BACK UP OOOXXOOXOOO (8)
Vibrator	NONE	Marker Lights	LED - 5 PR TOP & BOTTOM
Mudflaps	STD (2)(3)(4)(5)(6) ACROSS REAR CHASSIS	MMTS	OVAL LED - PIVOT BRACKET
		Apron	NONE

CHASSIS SPECIFICATIONS

Model	TANDEM - SPREAD (7)	ABS	2S / 1M	Tire Carrier	NONE
Length	PER ENGINEERING	Independ. Susp(s)		Landing Gear	2 SPEED JOST ALUMILIGHT X D/S CRANK
Width	102"		NONE	Elec Coupler	7 WAY + 7 WAY ISO LABELED 'AUXILIARY'
Draft Arms	ALUMINUM	Distance:		Hyd Hose Fitting	WINGNUT
Hoist	85-285	From:		Hyd Hose Length	108"
King Pin Setting	16"	Controls		Tow Hooks	NONE
5TH WP	3/8"	Location		Paint	BLACK
5th Whl Ht	49"	Axle(s)		Chassis Options:	
Rear Axle Setting	21.5"	Accessories			
K/P To Rear Axle	442-1/2"	Brakes			
Suspension	AAT30K / E2 / L- LIFT (9)(10)(11)	Drums			
Susp Control	FRAME + ELEC CC (9)(10)	Hubs			
Susp Spacing	121"	Wheels			
Susp Options	GALVANIZED HANGERS(12)	Tires			
Springs	AIR				
Axles	TP SPINDLES				
Accessories	NONE				
Brakes	16-1/2" x 7"				
Drums	CAST				
Hubs	10 STUD LWSTEEL				
Wheels	8.25 X 22.5 8 CB				
Tires	11R 22.5 R196A 14 PLY BS				

REMARKS:

- LATCH BAR GREASE: REMOTE ZERKS (073-70003-00) REMOTE FITTINGS TO THREE BEARINGS.
- 30" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AHEAD OF EACH AXLE. REF PIC BELOW. WEIGHT: 12,223
- CENTER ALUMINUM CHASSIS FLAP AHEAD OF EACH AXLE W/ BLACK RUBBER ON BOTTOM-REF PIC BELOW.
- 30" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM REARWARD OF FORWARD AXLE-REF PIC BELOW.
- CENTER ALUMINUM CHASSIS FLAP REARWARD OF FORWARD AXLE W/ BLACK RUBBER ON BOTTOM-REF PIC BELOW.
- ALL ALUMINUM OUTWARD FLAPS AND CENTER FLAPS TO BE FLUSH HORIZONTALLY AND VERTICALLY.
- BOLT ON SUBFRAME COVER.
- LIGHT PANEL TO BE ALL 4" LED AND SPACED EVENLY

9. TAILGATE, SUSPENSION EXHAUST, LIFT AXLE (W/ BRAKE RELEASE) ALL TO BE FRAME SWITCHES AND ELECTRIC CAB CONTROL WIRED TO AUXILIARY PLUG.
10. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX ON D/S BETWEEN SPREAD.
11. AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND MOUNTED AT COUPLER PLATE.
12. STRAP STOPS ON FRONT AXLE ONLY.



DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.