



Hale Trailer Brake & Wheel

071372-071377



EAST GENESIS UNLOADER TRAILER

OPEN TOP

CLOSED TOP

"GENESIS"

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM-FRONT LIFT
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	100	STYLE	GENESIS	AXLE TO AXLE	52"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	26.5"
FRONT	0.150	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE	0.150	GATESEAL	YES	PIN SETTING	36" + 3/8" KP PLATE
REAR	0.150	GATE LADDER	CAST / CENTER	SUSPENSION	AAT30K/E2/L-LIFT-E1(8)
POLISHED SIDES	NO	TARP HOOKS	NONE	SPRINGS	AIR
ROOF	NONE	WINDERS	ONE	AXLES	TP SPINDLES
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	MAXX 22T ADB
BULKHEAD	3/16" (1)(10)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO - MIDDLE &	ABS	2S / 1M
TARP	NONE		REAR-BOTH TUBE	HUBS	10 S LW STL-HXL-5
CATWALK	YES		TYPE		WHEEL END PKG
B.H. LADDER	D/S-COMMERCIAL	COMPACTOR:		WHEELS	8.25 X 24.5 (9)
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		
FLOOR MAKE	KEITH - 3" DRIVES	CENTER LATCH		TIRES	11R 24.5 R196A
FLOOR MAT'L	#2299+STD 'T' BLOCKS	PIN DIA.			BRIDGESTONE
WEARPADS	CWS	HYDRAULICS:		DOLLIES	2 SPEED HOLLAND
TAPE COLOR	BLUE IN TOP RAIL	HOSES	TWO-4000 PSI	LOCATION	MARK V D/S CRANK
LIGHT PANEL	LED IN TAILGATE (4)	LENGTH	156"	BUMPER	STEEL
MARKER LIGHTS	LED (4)	FITTINGS	PUSH-PULL	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60 (4)	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	YES (6)	LP	1" FEMALE	PAINT	SILVER
HOSE HANGER	YES-ON BULKHEAD	HOSE LOCATION	DRIVER SIDE		
TIRE CARRIER	NONE	AIR & ELECTRICAL	CENTER		

REMARKS:

1. NO INSIDE BULKHEAD STEPS.
 2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
 3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING.
 4. 3 PAIR LED PER SIDE SIDE TOP & BOTTOM WITH PROTECTORS. GROMMETS ALL PLACES WHERE WIRE PASSES THROUGH METAL.
 5. FILTERED GLAD HANDS.
 6. ADD CENTER CHASSIS MUDFLAP
 7. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
 8. AAT30K/E2/ L-LIFT-E1. MANUAL EXHAUST SWITCH ON D/S SUBFRAME TO EXHAUST SUSPENSION. MANUAL SWITCH ONLY FOR FRONT AXLE LIFT.
 9. 4 STEEL DISC WHEELS ON INSIDE, 4 CLEAN BUFF WHEELS ON OUTSIDE. USE PLASTIC INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
 10. ADD ACCESS HOLE IN FRONT D/S OF BULKHEAD THROUGH 5TH WHEEL PLATE BAND FOR FUTURE ACCESS TO HYDRAULIC TUBES.
- FINISH OFF WITH SMALL COVER PLATE SECURED WITH TEC SCREWS.

OVERALL HEIGHT (FT) **12.92** **EMPTY WEIGHT (#)** **17,245** **CUBIC YARDS** **112**
 (EMPTY WEIGHT VARIANCE +/- 3%)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.