



Hale Trailer Brake & Wheel

071378-071387



EAST UNLOADER TRAILER

OPEN TOP ☒

CLOSED TOP ☐

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUMINUM
HEIGHT (INCHES)	96	STYLE	SHEET & POST	AXLE TO AXLE	52"
SIDE MAT'L	3/16"	MAT'L THICKNESS	3/16"	REAR AXLE SETTING	26-1/2"
TOP RAIL	UNLOADER	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
ROOF	NONE	GATESEAL	NONE	PIN SETTING	36" W/ 3/8" PLATE
ROOF MAT'L		GATE LADDER	CAST / CENTER	SUSPENSION	AAT30K / E2-1 (10)
BULKHEAD	3/16" (1)(7)	TARP HOOKS	NONE	SPRINGS	AIR
TARP HOOKS	NONE	WINDERS	ONE	AXLES	TP SPINDLES
TARP BASKET	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
TARP	NONE	GATE CONTROL	MECHANICAL	DUSTSHIELDS	YES
CATWALK	YES	POCKETS	FABBED / EXTRUDED	BRAKE CHAMBERS	STD
B.H. LADDER	D/S-COMMERCIAL	CROSSPIPE (S)	TWO	ABS	2S / 1M
CROSSMEMBER	"I" BEAM -12" C/L	TUBE TYPE		HUBS	10 S STL/CAST-PIL
FLOOR MAKE	KEITH (8)				EAST ELITE
FLOOR MAT'L	2299	COMPACTOR:		WHEELS	8.25 x 24.5
WEARPADS	CWS	SIDE LATCH			NOTE (11)
HORIZONTALS	NONE	CENTER LATCH		TIRES	11R 24.5 R196
45° DIRT SHEDDERS	8" SMOOTH	PIN DIA.			BRIDGESTONE
TARP BAR	YES			DOLLIES	2 SPEED HOLLAND
TAPE COLOR	BLUE	HYDRAULICS:		LOCATION	MARK V - D/S CRNK
LIGHT PANEL	IN TAILGATE (4)	HOSES	TWO 4000 PSI	BUMPER	STEEL
MARKER LIGHTS	3 PR BOXED IN (4)	LENGTH	144"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES (4)	FITTINGS	PUSH-PULL	PUSH BLOCKS	YES (9)
MUDFLAPS	STD + (9)	HP	1" MALE	PAINT	SILVER
HOSE HANGER	ON BULKHEAD	LP	1" FEMALE		
TIRE CARRIER	NONE	HOSE LOCATION	DRIVER SIDE		
		AIR & ELECTRICAL	DRIVER SIDE		

REMARKS: REF# E11252 67207

1. NO INSIDE BULKHEAD STEPS.
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING.
4. 3 PAIR PER SIDE LED TOP & BOTTOM. **GROMMETS IN ALL LOCATIONS WHERE WIRE PASSES THROUGH METAL.**
5. FILTERED GLAD HANDS.
6. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
7. ADD ACCESS HOLE IN FRONT DRIVERS SIDE OF BULKHEAD THROUGH 5th WHEEL PLATE BAND FOR FUTURE ACCESS TO STEEL HYDRAULIC TUBES. FINISH OFF WITH SMALL COVER PLATE SECURED WITH TEC-SCREWS.
8. KEITH 2299 WITH 3" DRIVE CYLINDERS AND STANDARD NYLON "T" BLOCKS
9. ADD REAR CENTER CHASSIS MUDFLAP
10. MANUAL EXHAUST SWITCH ON D/S SUBFRAME
11. 4 STEEL DISC INSIDE, 4 CLEAN BUFF ALUMINUM DISC OUTSIDE. ADD PLASTIC INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.

OVERALL HEIGHT (FT) **12.58** **EMPTY WEIGHT (#)** **16,089** **CUBIC YARDS** **104**

BODY/FABR (INSPECTION FRAME IN LENGTH) TIRES/PAINT/ACID

(EMPTY WEIGHT VARIANCE ± 3%)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.