



# Hale Trailer Brake & Wheel

071471-071502



## ALUMINUM "BST" PLATFORM TRAILER

<b>LENGTH:</b>	48'	<b>SUSPENSION:</b>	AAT25K / E-2-1- HXL-5 (3)(6) GALVANIZED HANGERS
<b>WIDTH:</b>	102" Offset Air & Electric To D/S Nose Channel	<b>LOWERING KIT:</b>	AUTOMATIC
<b>NOSE:</b>	SQUARE - 7 WAY + AUX ISO 7 WAY OFF SET AIR AND ELECTRIC TO DRIVERS SIDE	<b>AXLE TO AXLE:</b>	98"
<b>KING PIN SETTING:</b>	30" w/ 1/4" PLATE	<b>AXLE TO REAR:</b>	30"
<b>FLOOR:</b>	HD KNURLED ALUM W/ 2 NAILERS INTEGRATED-- DBL "L" SIDE RAIL CENTER TIE DOWN TRACK	<b>LIFT / AXLE:</b>	NONE
<b>XMEMBER SPACING:</b>	22" SPACING	<b>SPACING:</b>	
<b>COIL PACKAGE:</b>	YES + 6 FLOOR INSERTS X 44'	<b>F.W. HEIGHT:</b>	49"
<b>SPOOLS:</b>	DOUBLE	<b>CONTROLS:</b>	
<b>POCKETS:</b>	STD H.D.	<b>AXLES:</b>	TP SPINDLES TIRE MAXX PRO BOTH AXLES
		<b>AUTO SLACKS:</b>	HALDEX (TSE Omnibrake LTRT Long Stroke Chmbr)
<b>TIE DOWNS:</b>	12 PAIR WITH 2 STORAGE PIPES	<b>BRAKES:</b>	16-1/2" X 7" EXTENDED LIFE
<b>MARKER LIGHTS:</b>	LED - 2 PR + MMTS (2)	<b>ABS SYSTEM:</b>	BENDIX TABS-6 2S/1M ABS BENDIX SR-5 BRAKE VALVE
<b>MID TURN SIGNAL:</b>	COMBO MRKR MMTS (2)	<b>HUBS:</b>	10 STUD STEEL - PILOTED (3) CAST DRUMS - PILOTED (4)
<b>LIGHT PANEL:</b>	OOS 000 SOO - LED W/ STAINLESS RINGS(2) FULL WIDTH BUMPER REAR ACCESS STEPS W/ LOCKDOWN LID	<b>WHEELS:</b>	8.25 X 22.5 ALUM - ALL CLEAN BUFF TR-572 VALVE STEM / V2B VALVE CAPS
<b>BULKHEAD:</b>		<b>TIRES:</b>	295 / 75R X 22.5 BS R-196A 14-PLY TIRE MAXX PRO BOTH AXLES
<b>TYPE:</b>	NONE	<b>LANDING GEAR:</b>	JUST A-450 D/S CRANK (5)
<b>HEIGHT:</b>		<b>TIRE CARRIER:</b>	NONE
<b>RETURNS:</b>		<b>TOOLBOX:</b>	<b>QTY:</b> NONE
<b>MAT'L:</b>		<b>SIZE:</b>	
<b>ACCENT TAPE:</b>	BLACK	<b>LOCATION:</b>	
<b>PAINT:</b>	BLACK	<b>MAT'L:</b>	
<b>WINCH TRACK:</b>	INTEGRATED BOTH SIDES DOUBLE 'L' RAIL BOTH SIDES	<b>MUDFLAPS:</b>	STD
<b>LOCATION:</b>		<b>TYPE:</b>	SILVER PLASTIC
<b>WINCHES:</b>	24-STEEL ZINC COATED SLIDING(12 EA. SIDE)	<b>LOCATION:</b>	ON REAR
<b>STRAPS:</b>	NONE		

### REMARKS:

1. CONSPICUITY TAPE ON MAIN BEAM NOT ON TARP BAR
2. ALL LIGHTS TO HAVE STAINLESS RINGS-ATTACHED WITH STAINLESS RIVETS. ALL BOXED IN BELOW RAIL. **WEIGHT:** 9709
3. HENDRICKSON HXL 5 PACKAGE WITH SEMI FLUID GREASE
4. STEMCO #650-0610 HUBOMETER D/S FRONT AXLE.
5. MOUNT LANDING GEAR 126" FROM THE FRONT OF TRAILER TO C/L OF LANDING GEAR. ADD GEAR TRUCKLITE #97960 MOUNTED D/S @ LANDING GE
6. REAR DECK HEIGHT SET AT 56" FOR ADDITIONAL GROUND CLEARANCE.

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.