



Hale Trailer Brake & Wheel

071999-072000

**GENESIS FRAMELESS DUMP****BODY SPECIFICATIONS**

Length	40'			Body	* FRONT TARP CAP W/ 12" RISE
Width	102" INBOARD	Tarp	NONE	Accessories	
Side Height	72" SOLID	Bow Holders	NONE		* REAR ALUM CAP W/ 12"
Top Rail	9" DUMP	Tarp Bows	NONE		RISE WELDED TO GATE
Side Matl-front	20' - .100" WALL	Tarp Basket	NONE		
-middle	10' - .140" WALL	Tarp Hooks	NONE		TAILGATE
-rear	10' - .180" WALL	Bulkhead Mat'l	3/16"	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOR DO NOT	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" (3/8" LAST 10')	Options	STEP UNDER DOOR	Slope	NONE
		Body Fenders	SQUARE OFF	Hinges	OVERSLUNG
Crsmbr Spacing	12" (10" CROSSMEMBER SPACING OVER SUSPENSION	Ladders (Out)	SHIP 5 STEPS LOOSE	Side Swing	YES-INTRL GRND CTRL-P/S HINGE
Floor Options	* FLOOR STRINGERS-FOUR ROWS OF 2" PLATES	Inside	NONE	Gateseal	RUBBER
		Shovel Hgr	NONE	Safety Latch	ONE EACH SIDE
Tailgate Control	AIR FRAME+ ELEC CC (1)(9)(10)			Coal/Grain Door	20"
Body Pkg	NONE	Light Panel	FULL - LED		
Options			OOO ooo OOO (8)	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 6 PR BOTTOM & TOP	Gate Options	NONE
Mudflaps	STD (2)(3)(4)(5)(6) ACROSS REAR CHASSIS	MMTS	OVAL LED - PIVOT BRACKET		
		Apron	NONE		

CHASSIS SPECIFICATIONS

Model	TANDEM - SPREAD (7)	ABS	2S / 1M	Tire Carrier	NONE
Length	PER ENGINEERING			Landing Gear	2 SPEED JOST ALUMILIGHT X D/S CRANK
Width	102"				
Draft Arms	ALUMINUM	Independ. Susp(s)			
Hoist	95-280		NONE		
		Distance:		Elec Coupler	7 WAY + 7 WAY ISO LABELED 'AUXILIARY'
King Pin Setting	16"	From:			
5TH WP	1/4"			Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"			Hyd Hose Length	108"
		Controls		Tow Hooks	NONE
Rear Axle Setting	21.5"			Paint	BLACK
K/P To Rear Axle	442-1/2"	Location			
Suspension	AAT30K / E2 / L- LIFT (9)(10)(11)	Axle(s)			
Susp Control	FRAME + ELEC CC (9)(10)			Chassis	
Susp Spacing	121"	Accessories		Options:	
Susp Options	GALVANIZED HANGERS(12)				
Springs	AIR	Brakes			
Axles	TP SPINDLES	Drums			
Accessories	25,000# GAWR	Hubs			
Brakes	16-1/2" x 7"				
Drums	CAST	Wheels			
Hubs	10 STUD LWSTEEL				
		Tires			
Wheels	8.25 X 24.5 8 CB				
Tires	11R 24.5 HSR2 16 PLY CONT				

REMARKS:

1. LATCH BAR GREASE: REMOTE ZERKS (073-70003-00) REMOTE FITTINGS TO THREE BEARINGS.	WEIGHT: 12,223
2. 30" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AHEAD OF EACH AXLE.	
3. CENTER ALUMINUM CHASSIS FLAP AHEAD OF EACH AXLE W/ BLACK RUBBER ON BOTTOM.	
4. 30" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM REARWARD OF FORWARD AXLE.	
5. CENTER ALUMINUM CHASSIS FLAP REARWARD OF FORWARD AXLE W/ BLACK RUBBER ON BOTTOM.	
6. ALL ALUMINUM OUTWARD FLAPS AND CENTER FLAPS TO BE FLUSH HORIZONTALLY AND VERTICALLY.	
7. BOLT ON SUBFRAME COVER.	CHANGE 1
8. LIGHT PANEL TO BE ALL LED	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

9. TAILGATE, SUSPENSION EXHAUST, LIFT AXLE (W/ BRAKE RELEASE) ALL TO BE FRAME SWITCHES AND ELECTRIC CAB CONTROL WIRED TO AUXILIARY PLUG.
10. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX ON D/S BETWEEN SPREAD.
11. AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND MOUNTED AT COUPLER PLATE.
12. STRAP STOPS ON FRONT AXLE ONLY.
13. DO NOT INSTALL CROSSOVER KIT

