



Hale Trailer Brake & Wheel
072033-072034



GENESIS FRAMELESS DUMP

BODY SPECIFICATIONS

Length	40'			Body	* FRONT TARP CAP W/ 12" RISE
Width	102" INBOARD	Tarp	NONE	Accessories	AND 10 MARKER LIGHTS
Side Height	78" SOLID	Bow Holders	NONE		* REAR ALUM CAP W/ 12" RISE
Top Rail	9" DUMP	Tarp Bows	NONE		BOLTED TO GATE & W/ 10 LIGHTS
Side Matl-front	20' - .100" WALL	Tarp Basket	NONE		WIRED AS CLEARANCE.
-middle	10' - .140" WALL	Tarp Hooks	NONE	TAILGATE	
-rear	10' - .180" WALL	Bulkhead Mat'l	3/16"	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOOR	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4"	Options		Slope	NONE
Crsmbr Spacing	12"	Body Fenders	SQUARE OFF	Hinges	OVERSLUNG
		Ladders (Out)	NONE	Side Swing	YES-INTRL GRND CTRL-P/S HINGE
		Inside	NONE	Gateseal	RUBBER
Floor Options	ADD 1/4" X 8" CLEANOUT			Safety Latch	ONE EACH SIDE
		Shovel Hgr	NONE	Coal/Grain Door	20"
Tailgate Control	AIR FRAME+ ELEC CC (1)(9)(10)	Light Panel	FULL - LED; X=LED BACK UP OOOOXOOOXOOOO (8)	Coal Chute	NONE
Body Pkg	NONE	Marker Lights	LED - 12 PR BOTTOM	Gate Options	NONE
Options		MMTS	OVAL LED - PIVOT BRACKET		
Vibrator	PREP FOR FUTURE COUGER DC3200	Apron	NONE		
Mudflaps	STD (2)(3)(4)(5)(6) ACROSS REAR CHASSIS				

CHASSIS SPECIFICATIONS

Model	TANDEM - SPREAD (7)	ABS	2S / 1M	Tire Carrier	NONE
Length	PER ENGINEERING			Landing Gear	2 SPEED JOST ALUMILIGHT X D/S CRANK
Width	102"				
Draft Arms	ALUMINUM	Independ. Susp(s)			
Hoist	85-285		NONE		
5TH WP		Distance:		Elec Coupler	7 WAY + 7 WAY ISO LABELED 'AUXILIARY'
King Pin Setting	16"	From:			
				Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"	Controls		Hyd Hose Length	108"
				Tow Hooks	NONE
Rear Axle Setting	21.5"	Location		Paint	BLACK
K/P To Rear Axle	442-1/2"	Axle(s)			
Suspension	AAT30K / E2 / L- LIFT (9)(10)(11)				
Susp Control	FRAME + ELEC CC (9)(10)	Accessories		Chassis	
Susp Spacing	121"			Options:	
Susp Options	GALVANIZED HANGERS(12)				
Springs	AIR	Brakes			
Axles	TP SPINDLES	Drums			
Accessories	NONE	Hubs			
Brakes	16-1/2" x 7"				
Drums	CAST	Wheels			
Hubs	10 STUD LWSTEEL				
		Tires			
Wheels	8.25 X 24.5 8 CB				
Tires	11R 24.5 R196A 14 PLY BS				

REMARKS:

1. LATCH BAR GREASE: REMOTE ZERKS (073-70003-00) REMOTE FITTINGS TO THREE BEARINGS.	WEIGHT: 13,652
2. 40" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AND THREE 4" MODEL 40 LIGHTS WIRED AS MARKER AHEAD OF EACH AXLE. REF PIC BELOW.	
3. CENTER ALUMINUM CHASSIS FLAP AHEAD OF EACH AXLE W/ BLACK RUBBER ON BOTTOM AND FIVE 4" MODEL 40'S WIRED AS MARKERS-REF PIC BELOW.	
4. 40" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AND THREE 4" MODEL 40 LIGHTS WIRED AS BRAKE REARWARD OF FORWARD AXLE-REF PIC BELOW.	
5. CENTER ALUMINUM CHASSIS FLAP REARWARD OF FORWARD AXLE W/ BLACK RUBBER ON BOTTOM AND FIVE 4" MODEL 40'S WIRED AS BRAKES-REF PIC BELOW.	
6. ALL ALUMINUM OUTWARD FLAPS AND CENTER FLAPS TO BE FLUSH HORIZONTALLY AND VERTICALLY.	
7. BOLT ON SUBFRAME COVER.	CHANGE 1, 2, 3
8. LIGHT PANEL TO BE ALL 4" LED AND SPACED EVENLY	

9. TAILGATE, SUSPENSION EXHAUST, LIFT AXLE (W/ BRAKE RELEASE) ALL TO BE FRAME SWITCHES AND ELECTRIC CAB CONTROL WIRED TO AUXILIARY PLUG.
10. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX ON D/S BETWEEN SPREAD.
11. AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND MOUNTED AT COUPLER PLATE.
12. STRAP STOPS ON FRONT AXLE ONLY.





DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.