



## Hale Trailer Brake &amp; Wheel

072037-072038

## GENESIS HYBRID FRAMELESS



## BODY SPECIFICATIONS

Length	40'-6" (1)			Body	
Width	102"	Tarp	NONE	Accessories	NONE
Side Height	70" (2)	Bow Holders	NONE		
Top Rail	4.5" INVERSE INBOARD	Tarp Bows	NONE		
Side Mat'l-front	35'----.100 WALL	Tarp Basket	NONE		
-middle	xxxxx	Tarp Hooks	NONE	TAILGATE	
-rear	5'-----.140 WALL	Bulkhead Mat'l		Height	FULL -- HYBRID SHAPE
Side Options	NONE	Bulkhead	SLOPE NOSE	Mat'l Thkness	.140 GENESIS PANEL
Floor Mat'l	1/4" NOMINAL (6)	Options	MANDOOR - D/S	Slope	NONE
Crsmbr Spacing	NONE	Body Fenders	NONE	Hinges	OVERSLUNG
		Ladders (Out)	LAST PANEL D/S - (4)	Side Swing	NONE
Floor Options	NOTE (7)	Inside	NONE	Gataseal	RUBBER
				Safety Latch	ONE 45 DEGREE EACH SIDE
		Shovel Hgr	NONE		
Tailgate Control	AIR /FRAME+AIR CC (3)	Light Panel	FULL WIDTH REAR-VERTICAL	Coal/Grain Door	23-1/2" MINIMUM INSIDE
Body Pkg	NONE		S/T/T + 3 CENTER ID + SHIELD +		OPENING (5)
Options			1 PR NON LED B/U LIGHTS	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 5 PR BOTTOM	Gate Options	NONE
Mudflaps	REAR & AHEAD OF REAR	MMTS	IN PIVOT BRACKET - LED		
	AXLES	Apron	NONE		

## CHASSIS SPECIFICATIONS

Model	TANDEM - SPREAD-FRONT LIFT	ABS	4S / 2M	Tire Carrier	NONE
Length	PER ENGINEERING			Landing Gear	2 SPEED JOST AX-150
Width	102"				
Draft Arms	ALUMINUM	Independ. Susp(s)			D/S CRANK
Hoist	85-265		NONE		
		Distance:		Elec Coupler	7 WAY + X'TRA 6-WAY
King Pin Setting	16" - 47-1/8" KING PIN TO	From:			TO JUNCTION BOX IN REAR
	FRONT OF BULKHEAD				
5th Whl Ht	49"			Hyd Hose Fitting	WINGNUT
		Controls		Hyd Hose Length	108"
Rear Axle Setting	21.5"			Tow Hooks	NONE
K/P To Rear Axle	429" APPROXIMATE			Paint	BLACK
Suspension	AAT30K / E2/ L LIFT E1	Location			
Susp Control	FRAME SWITCH+AIR CC(3)	Axle(s)			
Susp Spacing	121"				
Susp Options	NONE	Accessories		Chassis	NONE
Springs	AIR			Options:	
Axles	TP SPINDLES	Brakes			
Accessories	NONE	Drums			
Brakes	BENDIX ADB 22X LT	Hubs			
Drums	N/A				
Hubs	10 STUD STEEL - PILOTED	Wheels			
Wheels	22.5 ALUM 4CB / 4P Durabrite	Tires			
Tires	11R 22.5 R196A 14 PLY BS				

## REMARKS:

- 41'-10" OUTSIDE / 39'-10" INSIDE (MEASURED FROM INSIDE TOP FRONT TO INSIDE BOTTOM REAR - ALONG TOP RAIL)
- 70" SOLID (MEASURED FROM HORIZONTAL PLANE FROM TOP OF TOP RAILS TO CENTER OF FLOOR---LOWEST POINT) WEIGHT: 11,966
- FRAME SWITCHES TO BE IN WEATHERPROOF BOX ON D/S SUBFRAME 2 FEET AHEAD OF REARMOST AXLE
- REAR WHEEL WELL SIDE SKIRTS w / STEP D/S
- COAL DOOR OPENING (INSIDE) MUST BE 23-1/2" MINIMUM WIDTH / REFERENCE #58627
- 1/4" FLOOR WITH 3/16" REAR OVERLAY REAR 15' - DELETE DURA PRO LINER

## DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.