



Hale Trailer Brake & Wheel

072177-072183

TK80ACS-34 Steel/Aluminum Combo Step Deck Trailer

13813-ACS-34

Overall Width: 102"
 Fully Loaded Deck Height: 34"
 Loaded Ground Clearance: 9"
 Capacity:
 2-axle: 80k Distributed
 3-axle: 85k Distributed

Upper Deck Crossmembers 18" O.C.
 Main Deck Crossmembers 12" O.C.
 Aluminum Rub Rail w/ Chain Spools
 Stake Pockets (24" O.C.)
 Full-Length Hook Track
 Anti-corrosion Barrier Between Aluminum & Steel

Item #	Category	Description	Weight (lbs)	Qty
13813	Open Deck	TK80ACS-34 Steel/Aluminum Combo Step Deck Trailer	9,575	
13818	Overall Length	52'-10" Overall Length	509	
13819	Aluminum Content	Standard Aluminum Content		
13821	Fifth Wheel / King Pin	14" Kingpin Setting (82"/88"/94" Swing Clearance w/ 10'/10'-6"/11' Upper Deck)		
13824	Fifth Wheel / King Pin	48 - 50" 5th-wheel Height		
13827	Upper Deck	10' Upper Deck Length		
13830	Main Deck	60k in 10' Concentrated Load Rating		
13832	Decking	Aluminum Decking w/ Flush Apitong Nailers		
13843	Tie Downs	Winch Track Stops: Removeable		
13835	Tie Downs	No Sliding D-Rings on Upper Deck		
13837	Tie Downs	No Sliding Winches on Upper Deck		
13839	Tie Downs	No Sliding D-Rings on Main Deck		
13842	Tie Downs	Sliding Winches on Main Deck (each)	96	12
13845	Tie Downs	No J-hooks		
13847	Tie Downs	No Stake Pockets on Rear		
13850	Suspensions	Tandem Axle: (1) 23k Air Ride w/ (1) 23k Air Ride Rear Slider	271	

13956	Suspensions	Suspension Set Ahead 42" w/ Underride Guard (California Legal for 52'-10" OAL, 14" KP, & 49"/121" Slider Spacing - Not Canadian Overhang Legal)	23	
13858	Suspensions	49" Closed / 121" Open (slider only)	(68)	
13861	Axles	Standard Axle		
13867	Brakes / Air	2S1M / 2S2M Anti-Lock Brake System		
13869	Brakes / Air	20k Drum Brakes (per axle)		
13871	Hub / Drum	Steel Hub-Piloted - Cast Drum (per axle)		
08182	Wheel Finish	6.75 x 17.5 8-hole steel disc wheel (inside)		
08194	Wheel Finish	6.75 x 17.5 8-hole polished (AIP) aluminum wheel (outside) (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel	(96)	4
10058	Spare Wheel	No spare wheel		
07907	Tire Size	235/75R17.5 - 18 ply HTL2 (tire only) (per tire)		
10059	Spare Tires	No spare tire		
13874	Spare Tire Carrier	No Spare Tire Carrier		
13876	Flaps, Mud Guards & Fenders	Mudflaps: Rear Axle Only (standard TK)		
13878	Landing Gear	Standard Two-Speed (crank road side)		
13879	Toolbox	No Toolbox		
13882	Bumper	No Non-Certified Bumper		
13884	Flagholders	Standard Flagholders (3 per side)		
13885	Document Holder	Document Holder: 4-1/2" Round		
13886	Lights / Electrical	LED Lights - DOT Required w/ Midturn & 3rd Taillight (XOX)		
08024	Paint	Black S7203 with white decals (735-432-039)		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.