



# Hale Trailer Brake & Wheel

072703-072704



## FRAME DUMP

|                  |                              |                |                            |                 |  |
|------------------|------------------------------|----------------|----------------------------|-----------------|--|
| Length           | 26' - STEEL TUB              | Tarp Bar       | NONE                       | Body            |  |
| Width            | 96"                          | Tarp           | NONE - SEE NOTE (2)        | Accessories     | 1 - 2" DIA. LIGHT IN EACH REAR POST      |
| Side Height      | 62" (60 + ANGLE)             | Bow Holders    | NONE                       |                 |  |
| Top Rail         | 1/4" x 4" x 6" (1)           | Tarp Bows      | NONE                       |                 |  |
| Side Material    | 1/4" AR 450                  | Tarp Basket    | NONE                       |                 |  |
|                  | ANGLE ON TOP RAILS           | Doghouse       | STD                        |                 | TAILGATE                                 |
|                  | BH & GATE FLUSH W/ ANGLES    | Bulkhead Mat'l | 1/4" AR 450 - SLOPE NOSE   | Height          | FULL + ANGLE                             |
| Side Options     | ANGLE-1/4" x 2-1/2" x 2-1/2" | Bulkhead       | DIAMOND PLATE HOIST COVER  | Mat'l Thkness   | 1/4" AR 450                              |
| Floor Mat'l      | 1/4" AR 450                  | Options        | BH & TG FLUSH W/ CAP ANGLE | Slope           | NONE                                     |
|                  | 24'-8" INSIDE FLOOR LGTH     | Body Fenders   | FRONT w / 10" RUBBER FLAP  | Hinges          | OVERSLUNG                                |
| Crsmbr Spacing   | 12" SPACING                  | Ladders (Out)  | RUNG STYLE-BULKHEAD D/S    |                 | AIR POWER LIFT - INTERNAL                |
|                  |                              |                | D/S REAR                   | Gate Seal       | NONE                                     |
| Floor Options    | 4" x 6" LONGITUDINALS        | Inside         | NONE                       | Safety Latch    | ONE EACH SIDE                            |
|                  | CENTER BOLSTER @             | Shovel Hgr     | NONE                       |                 | 14" UP FROM BOTTOM                       |
|                  | MIDDLE OF TOP RAIL           | Dirt Shedders  | ALUM SIDE SKIRTS - FULL    | Coal/Grain Door | NONE                                     |
| Tailgate Control | FRM SWITCH REAR PKT+Elec CC  | Light Panel    | NONE                       | Coal Chute      | NONE                                     |
| Body Pkg         | ALUM SIDE SKIRTS - FULL      | Marker Lights  | LED - 2 PR BOTTOM          | Gate Options    | 2" x 2" ANGLE ON TOP OF GATE             |
| Options          | LENGTH                       | MMTS           | INSTALL IN BOLSTER         |                 | SOLID WELD ON ANGLE                      |
| Vibrator         | NONE                         | Apron          | NONE                       |                 | Tailgate Switch To Be In Rear D/S Pocket |
| Mudflaps         | STD +                        |                |                            |                 |  |
|                  | ACROSS REAR CHASSIS          |                |                            |                 |  |

### CHASSIS SPECIFICATIONS

|                   |                            |                   |         |                  |                         |
|-------------------|----------------------------|-------------------|---------|------------------|-------------------------|
| Model             | TANDEM                     | ABS               | 4S / 2M | Tire Carrier     | NONE                    |
| Beam Mat'l        | 16" STEEL @ 31#/FT         |                   |         | Landing Gear     | 2 SPEED JOST A450       |
| Length            | 25' 6"                     |                   |         |                  | D/S CRANK               |
| Width             | 96"                        | Independ. Susp(s) |         | Chassis Lights   | 00 000 00               |
| Hoist             | 85-220                     |                   | NONE    |                  |                         |
| Chassis Neck      | TANDEM                     | Distance:         |         | Elec Coupler     | 7 WAY + ISO 7 WAY       |
| King Pin Setting  | 18"                        | From:             |         | Hyd Tank         | NONE                    |
| 5th Whl Plate     | 3/8" + 3" x 7" Hoist Tubes | Controls          |         | Hyd Hose Fitting | WINGNUT                 |
| 5th Whl Ht        | 51"                        |                   |         | Hyd Hose Length  | 108"                    |
| Overhang          | 6"                         | Location          |         | Tow Hooks        | NONE                    |
| Rear Axle Setting | 21-1/2"                    | Axle(s)           |         | Paint            | FRAME - BLACK           |
| K/P To Rear Axle  | 266.5"                     |                   |         |                  | BODY - BLACK            |
| Suspension        | AAT30K / E2-1              | Accessories       |         | Tarp Bar Tape    | N/A                     |
| Susp Control      | FRAME SWITCH + AIR CC      |                   |         | Chassis          |                         |
| Susp Spacing      | STD                        | Brakes            |         | Options:         |                         |
| Susp Options      | 25,000 # GAWR              | Drums             |         |                  | SQUARE OFF REAR CHASSIS |
| Springs           | AIR                        | Hubs              |         |                  |                         |
| Axles             | TP SPINDLES - 25K GAWR     | Wheels            |         |                  | MUDFLAP ON CHASSIS      |
| Accessories       | METAL HUBCAPS              |                   |         |                  |                         |
| Brakes            | 16-1/2" x 7"               | Tires             |         |                  |                         |
| Drums             | CAST                       |                   |         |                  |                         |
| Hubs              | 10 STUD STEEL              |                   |         |                  |                         |
|                   |                            |                   |         |                  |                         |
| Wheels            | 8.25 X 24.5 4 STL/4 CB (3) |                   |         |                  |                         |
| Tires             | 11R 24.5 HSR2 16 PLY (4)   |                   |         |                  |                         |

### REMARKS: REF E11247 67110

|   |                |
|---|----------------|
| 1. BOLSTER TO BE IN MIDDLE OF TOP RAIL  |                |
| 2. DRILL ACCESS HOLE & GROMMET AT TOP D/S OF BULKHEAD FOR FUTURE TARP WIRE THROUGH TOP RAIL TO REAR OF BODY |                |
| 3. STEEL INSIDE / CLEAN BUFF ALUMINUM OUTSIDE   | WEIGHT: 15,911 |
| 4. 11R 24.5 HSR2 16 PLY CONTINENTALS.   |                |
| 5. OIL FILLED AIR GAUGE PLUMBED TO SUSPENSION AND MOUNTED IN FRAME NEAR LANDING GEAR                        |                |

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.