



Hale Trailer Brake & Wheel
073000-073004
EAST UNLOADER



OPEN TOP ☒

CLOSED TOP ☐

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	96	HEIGHT	FULL	MODEL	TANDEM
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUMINUM
HEIGHT (INCHES)	100	STYLE	SHEET & POST	AXLE TO AXLE	49"
SIDE MAT'L	3/16"	MAT'L THICKNESS	3/16"	REAR AXLE SETTING	26-1/2"
TOP RAIL		S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
ROOF	NONE	GATESEAL	NONE	PIN SETTING	36"
ROOF MAT'L		GATE LADDER	CAST / CENTER	SUSPENSION	REYCO 21-B
BULKHEAD	3/16"	TARP HOOKS	NONE	SPRINGS	AIR
TARP HOOKS	NONE	WINDERS	ONE	AXLES	TP SPINDLES (4)
TARP BASKET	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
TARP	NONE	GATE CONTROL	MECHANICAL	DUSTSHIELDS	YES
CATWALK	YES-	POCKETS	FABBED / EXTRUDED	BRAKE CHAMBERS	TOP OF AXLE
B.H. LADDER	COMM/ DS	CROSSPIPE (S)	TWO	ABS	2S / 1M
CROSSMEMBER	"I" BEAM -12" C/L	TUBE TYPE		HUBS	10 S STL/CAST-PIL
FLOOR MAKE	KEITH (1)				EAST ELITE
FLOOR MAT'L	2299 "T" BLKS	COMPACTOR:		WHEELS	8.25" x 24.5"
WEARPADS	CWS	SIDE LATCH			STEEL DISC
HORIZONTALS	NONE	CENTER LATCH		TIRES	11R 24.5 R250ED (H)
45° DIRT SHEDDERS	8" SMOOTH	PIN DIA.			16 PLY BRIDGESTONE
TARP BAR	YES			DOLLIES	2 SPEED HOLLAND
TAPE COLOR	BLUE	HYDRAULICS:		LOCATION	MARK V - D/S CRNK
LIGHT PANEL	IN TAILGATE	HOSES	TWO 4000 PSI	BUMPER	STEEL
MARKER LIGHTS	NOTE (2)	LENGTH	144"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES	FITTINGS	PUSH-PULL	PUSH BLOCKS	YES
MUDFLAPS	STD + (3)	HP	1" MALE	PAINT	SILVER
HOSE HANGER	ON BULKHEAD	LP	1" FEMALE	CHASSIS MUDFLAP	CENTER REAR (3)
TIRE CARRIER	NONE				

REMARKS:

* WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.

1. INSTALL COMPLETE FLOOR 2299, WITH NYLON "T" BLOCKS, ALUMINUM DRIVE FRAME, STAINLESS STEEL HYDRAULIC TUBING

ADD 2 PAIR OF FLOOR SIDE RAIL BRACES AT DRIVE UNIT

2. 3 PAIR EACH SIDE TOP & BOTTOM, ALL BOXED IN & ALL LIGHTS TO BE LED. GROMMETS WHERE ALL WIRES PASS THROUGH ALUMINUM

3. ADD REAR CENTER CHASSIS MUD FLAP.

4. GAWR #23,000

5. STAINLESS STEEL HYDRAULIC TUBING.

OVERALL HEIGHT (FT) **12.92**

EMPTY WEIGHT (#) **16,974**
(EMPTY WEIGHT VARIANCE +/- 3%)

CUBIC YARDS **101**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.

