



# Hale Trailer Brake & Wheel

073005-073009

## EAST UNLOADER TRAILER

OPEN TOP

CLOSED TOP



BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	QUAD(9)
LENGTH (FEET)	50	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	100	STYLE	SHEET & POST	AXLE TO AXLE	NOTE (9)
SIDE MAT'L	3/16" S & P	MAT'L THICKNESS	3/16"	REAR AXLE SETTING	26-1/2"
TOP RAIL	UNLOADER	S / S HINGE ON	P/S 4-3-4	5TH WHEEL HT	49"
ROOF	NONE	GATESEAL	NONE	PIN SETTING	36" W/ 3/8" PLATE
ROOF MAT'L		GATE LADDER	CAST / CENTER	SUSPENSION	NOTE (9)
BULKHEAD	3/16" (1)(2)(3)(4)	TARP HOOKS	NONE	SPRINGS	NOTE (9)
TARP HOOKS	NONE	WINDERS	ONE	AXLES	TP SPINDLES (10)
TARP BASKET	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
TARP	NONE	GATE CONTROL	MECH	DUSTSHIELDS	YES
CATWALK	YES	POCKETS	FABBED / EXTRUDED	BRAKE CHAMBERS	STD
B.H. LADDER	D/S-COMMERCIAL	CROSSPIPE (S)	TWO - TUBE TYPE	ABS	4S / 2M
CROSSMEMBER	"I" BEAM -12" C/L			HUBS	10 S STL / CAST
FLOOR MAKE	KEITH - 3.5" DRVS				EAST ELITE
FLOOR MAT'L	2299(8)	COMPACTOR:		WHEELS	8.25" x 24.5"
WEARPADS	CWS	SIDE LATCH			STEEL DISC
HORIZONTALS	NONE	CENTER LATCH		TIRES	11R 24.5 R250ED
45° DIRT SHEDDERS	8" SMOOTH	PIN DIA.			16 PLY
TARP BAR	YES			DOLLIES	2 SPD HOL MARK V
TAPE COLOR	BLUE	HYDRAULICS:		LOCATION	D/S CRANK
LIGHT PANEL	LED IN TAILGATE	HOSES	TWO 4000 PSI	BUMPER	STEEL
MARKER LIGHTS	NOTE (5)	LENGTH	144"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	YES - LED	FITTINGS	PUSH-PULL	PUSH BLOCKS	YES
MUDFLAPS	YES- LO MOUNT AHEAD AXLE 1	HP	1" MALE	PAINT	SILVER
HOSE HANGER	YES	LP	1" FEMALE		
TIRE CARRIER	NONE	HOSE LOCATION	DRIVER SIDE		
		AIR & ELECTRICAL	CENTER		

### REMARKS:

- 1.INSTALL INSIDE BULKHEAD STEPS
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING.
4. ADD ACCESS HOLE FOR FUTURE ACCESS TO STEEL HYDRAULIC LINES
5. 3 PR LED LIGHTS TOP & BOTTOM, ALL BOXED IN, MAKE SURE TO INSTALL RUBBER GROMMETS WHERE WIRE PASSES THROUGH METAL.
6. FILTERED GLADHANDS
7. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
8. KEITH 2299 FLOOR W/ 3.5" DRIVE AND STANDARD NYLON 'T' BLOCKS. ADD DRIVE UNIT BRACE ON EACH SIDE
9. EXTEND SUBFRAME FROM REAR OF TRAILER TO BACK SIDE OF LANDING GEAR. RE LOCATE DRIVE UNT OPENING TO MISS ALL AXLES  
MAIN TANDEM TO BE A REYCO 21B HD SINGLE LEAF WITH 49" SPACING AND THE THE LIFT AXLES TO BE HT250 WITH DEXTER SSA SPACED 52"  
FROM TANDEM AND 52" BETWEEN LIFTS, WITH BRAKE RELEASE WHEN UP. LIFT AXLES OPERATED BY A SWITCH ON THE FRAME. TIRE WILL BE BS  
385/65 M864 WITH 12:25 X 22.5 ALUMINUM WHEELS
10. GAWR TO BE 23,000#S FOR NEW YORK 'R' PERMIT 46,000#S ON MAIN TANDEM, 18,740 ON LIFT STEERABLES

**OVERALL HEIGHT (FT)**      **12.92**                      **EMPTY WEIGHT (#)**      **22,223**                      **CUBIC YARDS**      **120**

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.