



# Hale Trailer Brake & Wheel

## 074186-074187

### EAST GENESIS TIPPER



#### "GENESIS"

BODY: WEDGE DESIGN		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	QUAD - (6)(10)
LENGTH (FEET)	52	TYPE	SINGLE	TYPE	ALUM SUB FRAME(6)
HEIGHT (INCHES)	101" TO 109"	STYLE	GENESIS	AXLE TO AXLE	49" - 49" - 49"
SIDE MAT'L (OUTBOARD)	GENESIS (9)(14)	MAT'L THICKNESS	0.150	REAR AXLE SETTING	72" (13)
FRONT	0.150	HINGES	OVERSLUNG ONLY	5TH WHEEL HT	51"
MIDDLE	0.150	SIDE SWING	NO	PIN SETTING	36" W/ 1/2" PLATE(20)
REAR	0.150	GATESEAL	YES	SUSPENSION	AAT30K/E4-3-2-1
POLISHED SIDES	NO	GATE LADDER	CAST STEPS / CTR	SPRINGS	AIR (11)
ROOF	NONE	TARP HOOKS	5 FRONT / 4 REAR	AXLES	TP SPINDLES (7) (8)
ROOF MAT'L	NONE	WINDERS	ONE EA. SIDE	BRAKES	HENDRICK. MAXX 22T
BULKHEAD	3/16" - (1)(15)(18)	GATE GUIDE	YES	DUST SHIELDS	YES
TARP HOOKS	NONE	GATE CONTROL	AIR	BRAKE CHAMBERS	REMARK (12)
TARP BASKET	NONE	POCKETS	EXTRUDED	ABS	2S/1M
TARP	NONE	CROSSPIPE(S)	ONE - MIDDLE	HUBS	10 S STL
CATWALK	YES-INTERMEDIATE		SPRING TYPE		HXL-5 WARRANTY
B.H. LADDER	YES-D/S			WHEELS	8.25" X 22.5"
G. H. PROTECTIVE SHIELD	YES - D/S		COMPACTOR:		16 STEEL WHEELS
CROSSMEMBER TYPE:		SIDE LATCH	N/A	TIRES	275/70R 22.5 X MULTI
"V" STYLE ON 9" SPACE	YES - (2)	CENTER LATCH			Z 18 PLY MICHELIN(7)
"I" BEAM ON 12" C/L	NO	PIN DIA.		DOLLIES	JUST ALUMLIGHT HD
FLOOR MAT'L	3/8" (19)			LOCATION	HX150 D/S CRANK (17)
ADD 1/4" x 5" CLEANOUT				DISTANCE FROM REAR	36' - 6"
TAPE COLOR	NONE			BUMPER	STEEL
LIGHT PANEL	LED - ON BODY (16)			TIPPER PADS	STEEL T (22)
MARKER LIGHTS	LED - (3)			TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60			PAINT	EAST BLACK
MUDFLAPS	YES (21)				SOFT COAT
TIRE CARRIER	NONE				

#### REMARKS: 117K GVWR

1. YES - INSIDE BULKHEAD STEPS
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. 3 PAIR PER SIDE BOTTOM ONLY WITH PROTECTORS.
4. FILTERED GLAND HANDS.
5. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S SUBFRAME.
6. RUN SUBFRAME ALL THE WAY TO LANDING GEAR.
7. TIREMAXX PRO SYSTEM ON ALL FOUR AXLES.
8. 23,000# GAWR FOR THE NEW YORK 'R' PERMIT
9. WEDGE DESIGNED SIDES.
10. ALL FOUR AXLES ARE FIXED AND HENDRICKSON AAT30K.
11. ALL FOUR AXLES TO BE GALVANIZED HANGERS
12. 30/30 BRAKE CHAMBERS ON ALL FOUR AXLES-2ND EMERGENCY BRAKE VALVE REQUIRED.
13. 43' FROM KINGPIN TO C/L OF REAR AXLE.
14. ALUMINUM SIDE LINER 3/16" X 10' X 72" HIGH
15. MANDOOK IN BULKHEAD-CENTER
16. LIGHT PANEL OOO ooo OOO
17. BETTS PS-1 REGISTRATION HOLDER @ D/S LANDING GEAR.
18. AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AIR BAGS AND MOUNTED (STEM MOUNT) NEAR GLADHANDS.
19. 3/8" FLOOR FRONT 42' AND ADD A 1/4" ALUMINUM OVER LAY THE LAST 10'
20. 36" 1/2" THICK GALVANIZED 5TH WHEEL PLATE AND INCLUDES REPLACEABLE KING PIN CHANGE 1
21. REAR MUDFLAPS MOUNTED 18" FORWARD FROM THE END OF THE FLOOR.
22. TIPPER PADS NEED TO BE 4" REARWARD OF LATCHES.
23. EXTRA BRACE/SUPPORT AT LANDING GEAR IN REGARDS TO THE SUBFRAME.

**OVERALL HEIGHT (FT) 13' - 6"**

**EMPTY WEIGHT (#) 21,130**  
( EMPTY WEIGHT VARIANCE +/- 3% )

**CUBIC YARDS 143**

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.