



## Hale Trailer Brake & Wheel 102810-102811



### TK80SA Advantage Plus! Sliding Axle trailer 12815-80SA AdvPlus

<p>12815 - STANDARD EQUIPMENT          Perimeter Frame Gooseneck Design          Capacity: 80,000 lbs uniform / 50,000 lbs in 10 ft.          37½" loaded deck height with 17.5 tires          42" loaded deck height with 22.5 tires          49" loaded 5th wheel height          9' 10" upper deck          16" kingpin setting with 80" swing clearance          Hydraulic sliding axles          Tilting main deck - forms a ramp to upper deck          6½° loading angle, 15° dump angle          Air Ride suspension          Air Ride lowering control panel on upper deck with liquid filled guage.          No traveling hydraulic lines for sliding axle operation          Side by side 2-stage cylinder, closed in travel position          Air and electrical lines contained in protective track          Single recessed winch roller at front of deck          Push button hydraulic valve controls (driver side only)          Full-function wireless remote          Central located lube system</p>	<p>4 beam main frame construction          3" I-beam crossmembers          Triangle cutouts          (2) 25,000 lb axles (5/8" wall)          4S2M ABS Brakes          Automatic slack adjusters          One-piece oil seals          Pro Tork axle nuts          80' winch cable with locking safety hook          Key hole slots on 24" centers in inner and outer beams          3/8" smooth approach plate          4-way slots on approach plate          2 side access tool boxes at front of upper deck          LED lights, 50 state legal          Electrical system per DOT regulations          Rubber mounted sealed lights with sealed harness system          Flag holders at rear          Mud flaps          Red &amp; white conspicuity markings          Paint- Trail King 2-part polyurethane</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Item #	Category	Description	Weight (lbs)	Qty
12815	Open Deck	TK80SA Advantage Plus! Sliding Axle trailer		
13124	Upper Deck	No Headboard		
10894	Fifth Wheel Height	49" loaded fifth wheel height		

10896	Winch	20,000 lb. hydraulic winch with level wind (mounted above king pin) Includes 9/16 x 80' cable		
10898	Winch	Winch guard		
13106	Winch	Winch Cable Skid Plate on Upper Deck		
10900	Hydraulics	PTO hydraulic tilt		
10906	Landing Gear	2 Speed park stands (crank curb side)		
10885	Overall Length	47'-11" overall length		
10891	Overall Width	102" wide		
13112	Main Deck	TK80SA+ 12" Cross member spacing		
9998	Decking, Main Deck	Alternative Option Selected. See Add'l Options Section Below.		
12821	Decking, Approach Plate	3/8" smooth approach plate		
13127	Axle Spacing	50" Axle Spacing		
13128	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)		
08182	Wheel Finish	6.75 x 17.5 8-hole steel disc wheel (inside)	4	
08192	Wheel Finish	6.75 x 17.5 8-hole steel disc wheel (outside)	4	
08205	Spare Wheel	6.75 x 17.5 8-hole steel disc wheel (per wheel)	54	
07907	Tire Size	Continental 235/75R17.5 - 18 ply HTL2	8	
08110	Spare Tires	Continental 235/75R17.5 - 18 ply HTL2 (tire only) (per tire)		
12878	Lights / Electrical	Mid-turn signal clearance lights		
12880	Lights / Electrical	3rd tail light package		
14630	Paint	Non-Metallic color match paint upcharge Yellow (Dupont #93-35686) with black decals TK#		

### 12815-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
10916	Tie Downs	Add exterior bent d-rings on 48" centers		
10922	Miscellaneous	Hubodometers		

63960	Custom Options	63960 - General - additional owners manual.	2
67752	Custom Options	TKSA+ Additional wireless remote (two total)	
12875	Miscellaneous	Add curbside push button hydraulic control pad with LED indicators	
13122	Miscellaneous	9" swingouts (Includes stiffener on the inside of the main beam behind swingout)	
68260	Custom Options	TK80SA+"Arrow" style mid-turns	
68261	Custom Options	TK80SA+ 1 3/4" apitong decking ILO 1 3/8"	
01080	Paint	Non-Metallic color match paint upcharge for 5th wheel trailers	
08009	Paint	Epoxy primer	
67753	Miscellaneous - Special	67753 SA - Back-up alarm	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.