



Hale Trailer Brake & Wheel 112950-112954



OLB36NGH - "Advantage Series - Heavy Duty Live Bottom 08599-OLB36NGH

08599 - Kingpin to Center of Last Axle: 35' 11"	36" Direct Drive Live Floor
Overall Length: 40' 9"	3" Pitch Roller Chain
Overall Height (w/ 48" fifth wheel and no hopper extensions): 10' 2"	2 Ply 3/8" Belt w/ Steel Z-Bar Support
Overall Width: 102"	Hydraulic Tap Chain Oiler
Capacity (w/o extensions): 40 cubic yards	Heavy Duty Pushblock
	Center Mud Flap

Item #	Category	Description	Weight (lbs)	Qty
08599	Materials Hauling	OLB36NGH - "Advantage Series - Heavy Duty Live Bottom Trailer	18,200	
08603	Fifth Wheel / King Pin	48" Fifth Wheel Height		
12807	Fifth Wheel / King Pin	Removeable Kingpin		
08606	Hopper Sheets	Rear Hopper Sheets: .160" AR450		
08611	Hopper Extensions	No Extensions w/ Universal Tarp Shelf	83	
08738	Exterior Sheeting	Aluminum Exterior Sheeting	217	
9998	Drive / Hydraulics	Alternative Option Selected. See Add'l Options Section Below.		
08625	Belt / Chain	HTORS Belt		
08627	Belt / Chain	Heavy Duty Chain Crossmembers (.160" Domex 100)		
08629	Tailgate / Controls	Lock & Lift Air Tailgate: Electric Cab Controls		
08635	Suspensions	Tri Axle: (1) 25k Steerable Front Lift (Regulated) w/ (2) 30k Air Ride w/ Liquid Filled Pressure Gauge	942	
08644	Suspensions	49" / 50" Spacing		
08650	Axles	5/8" Wall Axle - 25,000 lb Nominal Rating (per axle)		2

08653	Axles	23k STD Life Brakes w/ 6" Autoslacks (per axle)		3
08661	Brakes / Air	2S1M / 2S2M Anti-Lock Brake System		
08664	Brakes / Air	RM50 (automatic reverse control)		
08669	Hub / Drum	Duralite Hub-Piloted - Cast Drum (per axle)		3
08306	Down Axle Wheels (inside)	8.25 x 24.5 10-hole machined aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(60)	4
08308	Down Axle Wheels (outside)	8.25 x 24.5 10-hole polished aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(64)	4
08391	Lift Axle Wheels (inside)	No Inside Wheel Required (Outside wheels are Super Singles)		
08311	Lift Axle Wheels (outside)	12.25 x 22.5 Aluminum Polished .56" Offset (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(148)	2
08255	Down Axle Tires	11R24.5 Continental HSR-2 16 Ply (per tire) ILO Std Tire	152	8
08260	Lift Axle Tires	425/65R22.5 Continental HTR-2 20 Ply (per tire) ILO Std Tire	(36)	2
08704	Lights / Electrical	LED Lights - DOT Required w/ Midturn		
08686	Ladder	Ladder Over CS Fender (std location)		
08745	Tarps	Shurco "Shur Trak" Tarp, Electric	559	
08679	Flaps, Mud Guards & Fenders	Front Fender Mudflaps: Short Front, Long Rear		
08675	Flaps, Mud Guards & Fenders	Aluminum Front Fenders		
08678	Flaps, Mud Guards & Fenders	Plastic Half-Round Rear Fenders (per axle)	24	3
08683	Flaps, Mud Guards & Fenders	Rear Mudflaps: Post-Mounted Flip-Up		
08681	Flaps, Mud Guards & Fenders	Interior Mudflaps: None		
08685	Landing Gear	Two-Speed (crank road side)		
08691	Spray System	No Spray System		
08694	Document Holder	Document Holder: 4-1/2" Round		
08024	Paint	Black S7203 with white decals (735-432-039)		
08713	Decals	Black Logo and Stripe		

08599-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
08706	Lights / Electrical	Dual Halogen Spotlights (std location)	2	
08657	Axles	P Spindles (required w/ super single tires) (per axle)		3
08707	Lights / Electrical	Dual Strobe Lights (std location)	1	
08710	Lights / Electrical	Back-up Alarm - 107 db (std location)		
81633	Custom Options	81633 (OLBHH) 19.0 cu. Hydraulic Motor ILO std 15.0 cu. in Hydraulic Motor	12	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.