

HALE

TRAILER

BRAKE & WHEEL



Hale Trailer Brake & Wheel

113073-113075

OLB36NGH - "Advantage Series - Heavy Duty Live Bottom 08599-OLB36NGH

08599 - Kingpin to Center of Last Axle: 35' 11"	36" Direct Drive Live Floor
Overall Length: 40' 9"	3" Pitch Roller Chain
Overall Height (w/ 48" fifth wheel and no hopper extensions): 10' 2"	2 Ply 3/8" Belt w/ Steel Z-Bar Support
Overall Width: 102"	Hydraulic Tap Chain Oiler
Capacity (w/o extensions): 40 cubic yards	Heavy Duty Pushblock
	Center Mud Flap

Item #	Category	Description	Weight (lbs)	Qty
08599	Materials Hauling	OLB36NGH - "Advantage Series - Heavy Duty Live Bottom Trailer	18,200	
08603	Fifth Wheel / King Pin	48" Fifth Wheel Height		
12807	Fifth Wheel / King Pin	Removeable Kingpin		
08732	Hopper Sheets	Full Hopper Sheets: .160" AR450	383	
08611	Hopper Extensions	No Extensions w/ Universal Tarp Shelf	83	
08738	Exterior Sheeting	Aluminum Exterior Sheeting	217	
O9998	Drive / Hydraulics	Alternative Option Selected. See Add'l Options Section Below.		
08625	Belt / Chain	HTORS Belt		
08627	Belt / Chain	Heavy Duty Chain Crossmembers (.160" Domex 100)		
08629	Tailgate / Controls	Lock & Lift Air Tailgate: Electric Cab Controls		
08639	Suspensions	Quad Axle: (1) 25k Steerable Front Lift (Regulated) w/ (3) HD Spring (21b)	2,648	
O9998	Suspensions	Alternative Option Selected. See Add'l Options Section Below.		
08651	Axles	3/4" Wall Axle - 27,000 lb Nominal Rating (per axle)	90	3

08653	Axles	23k STD Life Brakes w/ 6" Autoslacks (per axle)		4
08661	Brakes / Air	2S1M / 2S2M Anti-Lock Brake System		
09998	Brakes / Air	Alternative Option Selected. See Add'l Options Section Below.		
08669	Hub / Drum	Duralite Hub-Piloted - Cast Drum (per axle)		4
15066	Down Axle Wheels (inside)	8.25 x 24.5 10-hole machined (SP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(90)	6
15067	Down Axle Wheels (outside)	8.25 x 24.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(96)	6
15098	Lift Axle Wheels (inside)	No Inside Wheel Required (outside wheels are Super Singles)		
15079	Lift Axle Wheels (outside)	12.25 x 22.5 (XP) Aluminum Polished .56" Offset (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(148)	2
16733	Down Axle Tires	Continental 11R24.5 HSR2 - 16 Ply (per tire) ILO Std General 11R22.5 HT - 14 Ply	228	12
16728	Lift Axle Tires	Continental 385/65R22.5 HT3 - 20 Ply (per tire) ILO Std General 11R22.5 HT - 14 Ply	(96)	2
08686	Ladder	Ladder Over CS Fender (std location)		
08704	Lights / Electrical	LED Lights - DOT Required w/ Midturn		
08745	Tarps	Shurco "Shur Trak" Tarp, Electric	559	
08675	Flaps, Mud Guards & Fenders	Aluminum Front Fenders		
08678	Flaps, Mud Guards & Fenders	Plastic Half-Round Rear Fenders (per axle)	32	4
08679	Flaps, Mud Guards & Fenders	Front Fender Mudflaps: Short Front, Long Rear		
08681	Flaps, Mud Guards & Fenders	Interior Mudflaps: None		
08683	Flaps, Mud Guards & Fenders	Rear Mudflaps: Post-Mounted Flip-Up		
08685	Landing Gear	Two-Speed (crank road side)		
08691	Spray System	No Spray System		
08695	Document Holder	Document Holder: 12" x 14" Flat	3	
08009	Paint	Epoxy primer		
08024	Paint	Black S7203 with white decals		
08713	Decals	Black Logo and Stripe		

08599-Additional Options

Item #	Category	Description	Weight (lbs)	Qty
08657	Axles	P Spindles (required w/ super single tires) (per axle)		4
08706	Lights / Electrical	Dual Halogen Spotlights (std location)	2	
08707	Lights / Electrical	Dual Strobe Lights (std location)	1	
08710	Lights / Electrical	Back-up Alarm - 107 db (std location)		
80480	Axle Spacing - Special	80480 (OLBNG-HH) 121"/50"/49" Axle Spacing	230	
81626	Suspensions / Axles - Special	81626 (All OLB) No Automatic Reverse Control - Steerable Axle		
81633	Drive / Hydraulics - Special	81633 (OLBHH) 19.0 cu. Hydraulic Motor ILO std 15.0 cu. in Hydraulic Motor	12	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.