



Hale Trailer Brake & Wheel

TK100J -123481
TK120LPSD - 348223
'8" Front GN - L3482A
Rear GN - L3482B
30' Deck - L3482L
20' Deck - L3482M
10' Deck - L3482N

TK100J Jeep; No ABS, 100,000lb cap, (3 axles)
11942-100J

STANDARD EQUIPMENT

48" sliding 5th wheel 16" kingpin setting w/110" swing clearance Outboard 10-hole pilot mount 27,000 lb. axles (3/4" wall) Chain ups for axle 16 1/2" x 7" air Brakes Oil seal hubs Air ride suspension Automatic slack adjusters 96" wide	Electrical system per ICC/DOT regulations Rubber mounted sealed LED lights and sealed harness system Telescopic pin-type park stands Mud flaps Liquid-filled air gauge Air ride raise and lowering kit Pogo stick for air and electrical lines Four (4) D-rings for lifting Red & white conspicuity markings
---	--

Item #	Category	Description	Weight (lbs)	Qty
11942	Open Deck	TK100J Jeep; No ABS, 100,000lb cap, (3 axles)		
11958	Fifth Wheel	50" 5th-wheel height Height		
11965	Fifth Wheel / King Pin	Two kingpin settings (specify additional setting) <i>16" and 28" settings</i>		
11967	Hydraulics / Controls	Hydraulics through jeep to power gooseneck		
11978	Landing Gear	2-speed park stands (crank handle on curb side)		
11981	Deck Width	8' 6" wide (100J)		
11993	Axle Spacing	60" axle spacing <i>291" wheel base (KP to center axle)</i>		
11994	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)		
9999	Wheel Size	8.25 x 22.5 10-hole disc wheel		

15051	Wheel Finish (inside)	8.25 x 22.5 10-hole machined (SP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel		6
15052	Wheel Finish (outside)	8.25 x 22.5 10-hole polished (XP) aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel	(150)	6
10058	Spare Wheel	No spare wheel		
07913	Tire Size	Continental 275/70R22.5 HSR2 - 18 ply		12
10059	Spare Tires	No spare tire		
08009	Paint	Epoxy primer		
08024	Paint	Black S7203 with white decals		
14322	Paint	Plumb before paint		

Front GN

Item #	Category	Description	Weight (lbs)	Qty
75663	Custom Options	75663 TK170HDG - 23'-8" gooseneck with 14'-8" base and 9'-0" flip, PTO hydraulics 50" 5th wheel height		
73508	Custom Options	73508 TK170HDG - 13HP Honda SCU ILO std PTO hyd.		
71615	Custom Options	71615 TK140HDG - Transport Doors, build base doors for 4' unloaded G.C. ILO standard.		
75283	Custom Options	75283 TK160/170HDG - Gooseneck to have 15" stroke cylinders to increase lift of neck. Rear of upper frame will be higher to accommodate longer cylinders.		
02241	Main Deck	D-rings (ea.) 3 pair inside of G.N (both goosenecks) 2 pair on outside arch of GN (both goosenecks) 1 pair on back of GN D-rings (ea.) both goosenecks		12
08024	Paint	Black S7203 with white decals		
62262	Custom Options	62262 TK130-170HDG Hyd Assist for gooseneck flip.		
64292	Custom Options	64292 - HDG - Dual hydraulics with selector (diverter) valve. Requires self contained unit option.		

11942-Jeep Additional Options

Item #	Category	Description	Weight (lbs)	Qty
77297	Custom Options	77297 TK100J - Expanded metal in first 2 bays of the upper portion of the jeep GN, on top of the bottom flanges for storage.		
10927	Miscellaneous	PSI Tire Inflation System (3 axle)		
62308	Landing Gear - Special	62308 - General - Crank on drivers side ILO curb		
71530	Gooseneck - Special	71530 - TK100J - 84" Sliding Fifth Wheel plate, with 70K Vertical ILO STD 48" sliding fifth wheel plate		
76680	Flaps, Mud Guards & Fenders - Special	76680 TK100JLW - Black plastic fenders (like EFX ILO Poly)		

TK170, Full width, 18" beam depth

12270-TK170

TK170, Full width, 18" beam depth

TK170, Full width, 18" beam depth

Item #	Category	Description	Weight (lbs)	Qty
12270	Open Deck	TK170, Full width, 18" beam depth		
12271	Beam Depth	For correct beam depth, specify the Serial # of the corresponding trailer.		
13079	Type of Deck	Full width deck section, includes 4' storage area, 10 ga. Steel		
12987	Deck Length	30' deck length		
12992	Deck Width	10' deck width for 16' to 30' deck lengths		
12995	Main Deck	Flat deck includes triangle cut-outs		
13003	Main Deck	6' knuckle trough (not available on deck extensions)		
13004	Main Deck	Horizontal pins, detachable wheel area		
13023	Decking	2 1/2" Apitong raised decking (net) 16' to 30' deck lengths		
13006	Tie Downs	Standard cut-outs in beams		
13012	Outriggers / Side Extensions	Brackets only, for flatback removable outriggers, 24" OC (Ea.)		
13024	Ramps	No ramps		
12994	Concentrated Capacity	Concentrated in 10' (deck section only)		
13027	Lights / Electrical	LED light package (deck section only)		
08009	Paint	Epoxy primer		
08024	Paint	Black S7203 with white decals		

12270-30' Additional Options

Item #	Category	Description	Weight (lbs)	Qty
70936	Custom Options	70936 - TK150HDG - 24" deck height/6" ground clearance ILO 26"deck height/8" ground clearance		
02241	Main Deck	D-rings (ea.) 7 pair on main deck 2 pair inside center beams front and rear		18
74002	Custom Options	74002 HDG - 1 pair of Canadian style tie down. Inside dimensions are 4.5" x 2.5" x 9" tall		6
76266	Custom Options	76266 TK170HDG 30' FLAT DECK Concentrated in 10' - 18" deep beams ILO 20" deep beams. Deck will require triple stirrups @ the rear ILO single.		

TK170, Full width, 18" beam depth

12270-TK170

TK170, Full width, 18" beam depth

TK170, Full width, 18" beam depth

Item #	Category	Description	Weight (lbs)	Qty
12270	Open Deck	TK170, Full width, 18" beam depth		
12271	Beam Depth	For correct beam depth, specify the Serial # of the corresponding trailer.		
12272	Type of Deck	Full width deck extension		
12982	Deck Length	20' deck length		
12992	Deck Width	10' deck width for 16' to 30' deck lengths		
12995	Main Deck	Flat deck includes triangle cut-outs		
13002	Main Deck	No knuckle trough		
13004	Main Deck	Horizontal pins, detachable wheel area		
13023	Decking	2 1/2" Apitong raised decking (net) 16' to 30' deck lengths		
13006	Tie Downs	Standard cut-outs in beams		
13012	Outriggers / Side Extensions	Brackets only, for flatback removable outriggers, 24" OC (Ea.)		
13024	Ramps	No ramps		
O9998	Concentrated Capacity	Alternative Option Selected. See Add'l Options Section Below.		

13027	Lights / Electrical	LED light package (deck section only)
08009	Paint	Epoxy primer
08024	Paint	Black S7203 with white decals

12270-20' deck Additional Options

Item #	Category	Description	Weight (lbs)	Qty
02241	Main Deck	D-rings (ea.) 7 pair of D-rings		14
76267	Custom Options	76267 TK170HDG 20' Flat Deck Extension (Main Deck Concentrated in 10') - 18" deep beams ILO 20" deep beams. Requires double stirrups @ front and triple @ rear.		
74002	Custom Options	74002 HDG - 1 pair of Canadian style tie down. Inside dimensions are 4.5" x 2.5" x 9" tall		4

TK170, Full width, 18" beam depth

12270-TK170

TK170, Full width, 18" beam depth

TK170, Full width, 18" beam depth

Item #	Category	Description	Weight (lbs)	Qty
12270	Open Deck	TK170, Full width, 18" beam depth		
12271	Beam Depth	For correct beam depth, specify the Serial # of the corresponding trailer.		
12272	Type of Deck	Full width deck extension		
12974	Deck Length	10' deck length		
12991	Deck Width	10' deck width for 4' to 15' deck lengths		
12995	Main Deck	Flat deck includes triangle cut-outs		
13002	Main Deck	No knuckle trough		
13004	Main Deck	Horizontal pins, detachable wheel area		
13022	Decking	2 1/2" Apitong raised decking (net) 4' to 15' deck lengths		
13006	Tie Downs	Standard cut-outs in beams		
13012	Outriggers / Side Extensions	Brackets only, for flatback removable outriggers, 24" OC (Ea.)		
13024	Ramps	No ramps		
09998	Concentrated Capacity	Alternative Option Selected. See Add'l Options Section Below.		
13027	Lights / Electrical	LED light package (deck section only)		

08009	Paint	Epoxy primer
08024	Paint	Black S7203 with white decals

12270-10' deck ext Additional Options

Item #	Category	Description	Weight (lbs)	Qty
76268	Custom Options	76268 TK170HDG 10' Flat Deck Extension (Main Deck Concentrated in 10') - 18" deep beams ILO 20" deep beams. Requires double stirrups @ front and triple @ rear.		
74002	Custom Options	74002 HDG - 1 pair of Canadian style tie down. Inside dimensions are 4.5" x 2.5" x 9" tall		2
02241	Main Deck	D-rings (ea.)		8

0110140-ADB-14-Rear GN

Item #	Category	Description	Weight (lbs)	Qty
75664	Custom Options	75664 TK170 HDG/MDG, 26'-3" rear gooseneck, box beam design with recessed waffle plates, horizontal pins, deck to be approx 26"/6" deck height loaded, 44" beam centers to work with TK120LPSD-HS		
02241	Main Deck	D-rings (ea.) 4 pair inside of G.N (both goosenecks) 2 pair on outside arch of GN (both goosenecks) 1 pair on back of GN D-rings (ea.) both goosenecks		14

08024	Paint	Black S7203 with white decals
-------	-------	-------------------------------

62506 TK120LPSD-HS V1 Low Profile Steering Dolly

O9999-01-Add

Custom Option 1

Custom Option 1

0110140-ADB-14-TK120LPSD

Item #	Category	Description	Weight (lbs)	Qty
--------	----------	-------------	--------------	-----

62506	Custom Options	62506 TK120LPSD-HS V1 Low Profile Steering Dolly Load capacity – 120,000 lbs 10'-0" Wide 60" axle spacing, 14'-1" group spacing Front steer design Hydraulic steering 60 deg. (each way) hatbox rotation Auto steer or Manual steer 34 deg. 1st axle in auto, 39.5 deg. 1st axle in manual Adjustable steering ratio Manual steer by wireless or wire type remote Auto- alignment after manual steer Individual Poly fenders on all axles (24) - 235/75R 17.5 Radial tires (12) 6.75 X 17.5 Machine finished Aluminum wheels 12.25 X 7.5 brakes (20,000 GAWR) Air ride with raising and lowering 13HP Honda SCU 8" lift hydraulic hat box Push/tow bar at rear Aux air outlet for power tools Spring brakes on rear axles Power beyond for hydraulics Wide load sign brackets at rear	
65259	Custom Options	65259 TK120LPSD Add PSI System	
64688	Custom Options	64688, TK120LPSD-HS - Lightweight tow bar to pull down road empty	
65261	Custom Options	65261 - Polished aluminum 6.75 x 17.5 wheels on outside ilo of standard machined 6.75 x 17.5 wheels. This is for all 12 wheels.	
65182	Wheels / Tires - Special	65182 General - 245/70R17.5 Continental 18 ply tires ILO std. 235/75R17.5 Tires (Per Tire)	24
08024	Paint	Black S7203 with white decals	
76681	Custom Options	76681 TK120LPSD-HS - Black plastic fenders ILO poly (like new EFX)	
10061	Lights / Electrical	One pair of 4" round amber strobes at rear w/switch ILO 3rd tail light	
9999	Custom Options	Add (2) - 4 pole sockets in corners of dolly for strobe lights. Wired off of clearance lights, customer to supply lights	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.