



## Hale Trailer Brake & Wheel 197577-197626



ITEM	DESCRIPTION
<b>TYPE</b>	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
<b>DIMENSIONS</b>	
<b>LENGTH</b>	48'-0" closed.
<b>LENGTH</b>	80'-0" opened.
<b>OPENINGS</b>	5'-0" increments in closed position.
<b>WIDTH</b>	102", 97" between side rails.
<b>HEIGHT</b>	Floor, approximately 61 1/4" high at front and 58" at rear.
<b>COUPLING</b>	
<b>COUPLER PLATE</b>	5/16", plug welded structure.
<b>KING PIN LOCATION</b>	24" from front.
<b>COUPLER HEIGHT</b>	49".
<b>STRUCTURE</b>	Frame with "CAMBER".
<b>FLANGES</b>	Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high.
<b>FLANGES</b>	Male section (interior), 1/2" x 6", 100 000 psi steel, 17 5/8" high. (For tandem suspension Only)
<b>WEB</b>	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
<b>GOOSENECK</b>	12" high, with integrated nose ramp and 48" straight behind king pin.
<b>CROSSMEMBERS</b>	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. 710-065-G (CAPP T1J- xxxxx).
<b>FLOOR</b>	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
<b>FLOOR FASTENING</b>	Two screws per board at each crossmember.
<b>SIDE RAILS</b>	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Galvanized front and rear sills.
<b>SIDE BOXES</b>	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
<b>RUB RAILS</b>	3/8" x 2 1/2" shaped steel.
<b>CORNERS</b>	Bevelled.
<b>DIAGONAL BRACES</b>	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
<b>X BRACES</b>	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
<b>LOCKS</b>	Air operated with a third glad hand at front.
<b>ROLLERS</b>	4, 2 on female sections of frames and 2 on male sections.
<b>SPACERS FOR RUB RAILS</b>	Double between side boxes.
<b>ENDS</b>	
<b>FRONT RAIL</b>	Formed steel 1/4".
<b>BUMPER</b>	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
<b>BUMPER</b>	Aluminum plate, bolted between bumper uprights to close rear.
<b>POCKETS</b>	2 welded pockets at front for removable headboard.
<b>REAR RAIL</b>	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.





ITEM	DESCRIPTION
	"Automatic Tire Inflation Systems", REMARK: Make sure the system is adjusted to the same tires pressure written on the serial plate.
<b>ACCESSORIES</b> <b>REGISTRATION HOLDER</b> <b>WINCHES</b> <b>SLIDING TRACK</b> <b>MUD FLAPS</b>	One plastic, Betts-PS-1 or equivalent. Qty: 12, #HL-448M-00, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
<b>FINISHING</b> <b>PAINT</b>  <b>FINISHING</b>  <b>BOGIE</b> <b>HUBS</b> <b>WHEELS OR RIMS</b> <b>RETROREFLECTIVE TAPES</b>  <b>PAINTED AXLES</b>	No paint & no primer on the trailer. (extendable flat trailer only to be galvanized) Trailer prepared & shipped to be galvanized. (flat extendable trailer only) Color: Grey, code: PPG Q37-939514. Color: Grey, code: PPG Q37-939514. White. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. Color: Grey, code: PPG Q37-939514.
<b>ADDITIONAL OPTIONS</b>	SAME AS U#186613 EXCEPT ALL GALVANIZED
<b>CONFORMITY</b>	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.