



Hale Trailer Brake & Wheel 200643-200672



ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	90'-0" open
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, (exterior), 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, galvanized, 12" c/c.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	Galvanized 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" high. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Galvanized front and rear sills.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
X BRACES	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
SPACERS FOR RUB RAILS	Double between side boxes.
ENDS	
FRONT RAIL	Formed steel 1/4". (Galvanized)
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
BUMPER	Aluminum plate, bolted between bumper uprights to close rear.
POCKETS	2 welded pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL	



ITEM	DESCRIPTION
FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL REAR ADD. CONNECTOR	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, grounded to front connector, sealed beams Grote. (tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400). Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber. 4 way.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115), with mounting plate, galvanized. 10" x 11 1/2". Road side.
BOGIE BASIC SUSPENSION BOGIE SUSPENSION U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES MANUAL STOP BAR(S)	Slider, air ride suspension, tridem, 60" spread. Bogie tubing frame for suspension with 9" mounting height. (96" travel) Legal Canada-USA, (applicable for 53'telescopic) Hendrickson HT-250US (9), tridem, 60" spread. (Use only with slider bogie) With nuts at bottom. Air. AXN, TA250T, 22 000 lbs. capacity. Welded. 28 splines. 77 1/2". None (dia. 5"). 16 1/2" standard, AXN R23 extended life lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only). 10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. General, 11 R 24.5, RA 16 ply (43.4") (replace the S371) Two, Manac heavy duty, 1 5/8" diameter.
AIR SYSTEM GLAD HANDS AIR VALVES VALVE VALVE CONTROL BOX	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator. (2) Fast-brake kit. Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. *** Stainless steel ***



ITEM	DESCRIPTION
AUTOMATIC TIRE INFLATION	Automatic Tire inflation System Hendrickson Tiremax CP for axles with bearings HM 218248 & HM 212049, dual tires: Axles prep included for undressed axle. Maximum allowable tire pressure for this device is 120psi. (tandem) TIREMAX warning lamp installed on road side front rail. "Automatic Tire Inflation Systems", REMARK: Make sure the system is adjusted to the same tires pressure written on the serial plate.
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, KINEDYNE #1020ZP, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT FINISHING BOGIE HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES PAINTED AXLES	No paint & no primer on the trailer. Trailer prepared & shipped to be galvanized. *** Galvanized *** Gray Powder top coat white. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. Gray
ADDITIONAL OPTIONS	SAME AS U#197552 EXCEPT 24.5 TIRES **** Metal vin plate with pre-drilled holes in web prior to galvanizing.****
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.