



Hale Trailer Brake & Wheel 200673-200732



ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM LEGEND SD GALVANIZED SEE SECTION
DIMENSIONS LENGTH WIDTH HEIGHT	48'-0" 102", 97" between side rails. Floor, approximately 59 1/2" high at front and 54" at rear.
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	1/4", 80 000 psi steel, plug welded structure. 30" from front. 48".
STRUCTURE FLANGES WEB GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES RUB RAILS CORNERS X BRACES	44" c/c frame with "CAMBER". 3/8" x 5", high tensile. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 27" high at the peak. with holes, parachute shaped, to lighten trailer. 11 1/4" high, with integrated nose ramp and 48" straight behind king pin. I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanised, 12" c/c. Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative. Screws 10 gauge shaped 80 000 psi steel, 5" width x 5 11/16" height. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high, (USA Dimensions). Cargo pockets. 3/8" x 2 1/2" shaped steel. Bevelled. Between main beams, full length.
ENDS FRONT RAIL BUMPER HEADBOARD POCKETS BUMPER REAR RAIL	Formed steel, bolted. CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. *** Galvanized *** 2 bolted galvanised pockets at front for removable headboard. 2 rubber dock, at the end of rear rail. Formed steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS	7 way (SAE J560). Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.



ITEM	DESCRIPTION
ADDITIONAL OPTIONS	***** Vin plate to be made of metal. Pre-drill the web prior to galvanizing*
GALVANIZED CHOICES	Galvanized choices.
PLATFORM	Galvanized platform. (no paint) ** WARNING: holes parachute shaped required for dripping **
CROSSMEMBERS	Galvanized
FRONT RAIL	Galvanized
SIDE RAIL	Galvanized
REAR RAIL	Galvanized
BUMPER	Galvanized

CONFORMITY This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.