



# Hale Trailer Brake & Wheel

A008566-A008569

VIN:: 81199-81202



## GENESIS FRAMELESS DUMP

Length	36' (7)	BODY SPECIFICATIONS		Body	
Width	96" - INBOARD	Tarp	NONE	Accessories	NONE
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP STYLE	Tarp Bows	NONE		
Side Mat'l-front	4' ---- .100 MAT'L	Tarp Basket	NONE		
-middle	26' ---- .140 MAT'L	Tarp Hooks	NONE	TAILGATE	
-rear	6' ----- .180 MAT'L	Bulkhead Mat'l	3/16" MAT'L	Height	FULL
Side Options	NONE	Bulkhead	5" SLOPE PLATES	Mat'l Thkness	.140 GENESIS MAT'L
Floor Mat'l	1/4" FULL	Options	D/S-MANDOOK (5)	Slope	NONE
Crsmbr Spacing	12" SPACING	Body Fenders	SQUARE OFF	Hinges	OVERSLUNG
	10" SPACING IN SUBFRAME	Ladders (Out)	LAST PANEL D/S	Side Swing	YES W/ GRND CONTROL P/S
Floor Options	NONE	Inside	NONE	Gataseal	RUBBER
		Shovel Hgr	ONE-INSIDE ON P/S OF	Safety Latch	1 EA SIDE / 12" UP
			DOGHOUSE	Coal/Grain Door	NONE
Tailgate Control	FRAME SWITCH+ELEC CC	Light Panel	LED OOOOX ooo XOOOO	Coal Chute	NONE
Body Pkg	NONE		X= LED BACK UP LIGHTS	Gate Options	NONE
Options		Marker Lights	14-Pr. TOP + BOTTOM - LED		
Vibrator	NONE	MMTS	LED IN DRAFT ARM COVER		
Mudflaps	STD + ACROSS REAR +	Apron	NONE		
	ACROSS SUBFRAME (3)				

### CHASSIS SPECIFICATIONS

Model	TRIDEM- 1 FIXED & 2 FRNT LIFT	ABS	2S / 1M	Tire Carrier	NONE
Length	EXTENDED SUBFRAME(1)			Landing Gear	JOIST HX-150 D/S CRANK
Width	96"				
Draft Arms	ALUMINUM	Independ. Susp(s)			
Hoist	8-5-265 Top & Btm Rmt Grsr		NONE		
	NOTE (5)	Distance:		Elec Coupler	7-WAY + 7-WAY ISO-REF DWG
King Pin Setting	16"	From:			LABEL ACCESSORY
			LIFT KIT ON CENTER & FRONT	Hyd Hose Fitting	WINGNUT
5th Whl Ht	50"	Controls	AXLE FRAME SWITCH + ELEC C	Hyd Hose Length	108"
			BRAKE RELEASE VALVES(2)	Tow Hooks	YES - 1 EACH SIDE
Rear Axle Setting	21-1/2"		FRAME SWITCHES IN	Paint	BLACK
K/P To Rear Axle	418-1/2"	Location	WEATHERPROOF BOX D/S (6)		
Suspension	AAT30K / E-3 L(LIFT) E-2-1	Axle(s)	SUBFRAME AHEAD OF MOST		
Susp Control	FRAME SWITCH+ELEC CC		FORWARD AXLE	Chassis	MUDFLAP ACROSS REAR
Susp Spacing	52" - 52" (2)	Accessories		Options:	
Susp Options	GALVANIZED HANGERS				86,000 GVWR
Springs	AIR	Brakes			
Axles	TP SPINDLES	Drums			
Accessories	GREASED HUBS	Hubs			
Brakes	HENDR. MAXX 22 T ADB				
Drums	HXL-5 WHEEL END	Wheels			
Hubs	10 STUD LW STEEL				
	NOTE (4)	Tires			
Wheels	8.25 X 24.5 ALUM 6 HP/6 MP				
Tires	11R 24.5 HSR2 16-PLY CONT (8)				

### REMARKS:

1. EXTEND SUBFRAME AN EXTRA 24"
2. LIFT KIT ON CENTER AXLE AND FRONT AXLE - AXLES WILL NOT LIFT EVENLY AND CUSTOMER IS AWARE
3. FLAP ACROSS SUBFRAME AHEAD OF AXLE #1 -MUDFLAP TO BE MOUNTED 4" FORWARD OF STANDARD POSITION.
4. WHEEL GUARD INSULATORS BETWEEN HUBS & INSIDE ALUM WHEELS / HIGH POLISH MTD INSIDE - MIRROR POLISH MTD OUTSIDE
5. HOIST ACCESS TO BE AT INSIDE OF TRAILER AT THE REAR OF THE DOGHOUSE - NO OUTSIDE ACCESS HOLE
6. SEPARATE FRAME SWITCH AND SEPARATE ECC FOR EACH LIFT AXLE
7. ALL EAST LOGOS TO BE DECALS ONLY-NO WELD ON LOGOS
8. TIREMAXX PRO ON ALL AXLES - MOUNTED ON P/S SUBFRAME LIKE TRAILER 78145 (SEE PIC ATTACHED)

CHANGE 1

WEIGHT: 13,910

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

- 9. LATCH BAR GREASE ZERKS-REMOTE ZERKS TO D/S MANIFOLD
- 10. ALL FRAME SWITCHES IN BOX LOCATED @ P/S SUBFRAME
- 11. STEP BELOW MANDOOR TO BE LARGER STEP WITH SIDES (073-20176-00)
- 12. RIGHT WEIGH OIL FILLED GAUGE (LBS)(FLUSH MOUNT) ON D/S OF FRONT COUPLER PLATE

