



# Hale Trailer Brake & Wheel

## 395001-395250



Product : , , , ,

### GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
Product Type:	HT Composite

### GEOMETRY

Length - Exterior:	53'-0"
** Length - Interior:	52'-6" Nominal Lining To Lining
Width - Exterior:	102.36"
** Width - Interior:	101.5" Nominal Lining To Lining
Height - Exterior:	13'-6"
Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	107" from King Pin (+ 1"/-1/4")

### TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL21(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
* Wheel Finish for Steel:	Hot Dip Galvanized.
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
* Valve Stem & Cap:	TR-572 Valve Stem for use w/PSI

### UPPER COUPLER

Approach Plate:	1/4" thick 80,000 Lb Yield - 6 Support Channels
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
* Front Bottom Rail:	Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y:	(1) Tubing Application - Joggled

### BODY/BASE

Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Bay Area Crossmember Material:	Steel Crossmember
Running Gear C/M Size:	4" High
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'
Slider Body Rail (VT):	208" Rail Length

### FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
Floor Specification:	1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood
Floor Ratings - VT:	18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating

Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

---

**FRONT**

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid
Front Receptacle(7-Way):	Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug
Front Receptacle(7-Way) - Options:	Phillips QCS Plug connector
Gladhand/7-Way Location:	Overlaid on Lower Roadside Front
* Corner Radius Protector:	(2) 0.125" X 12" Alum Diamond Plate Each Side at Top

---

**SIDE**

Side Material:	6.5 mm thick Composite Panel, 80K PPW Galv. Steel, Both Sides w/ natural color rivets
Side Posts:	14 Gauge Galv Steel 'A' Slotted Logistic Insets with Composite Panel color matching Outer Closure (For Composite)
Side Post Centers:	48" C/L Stiffener (Side Closure) - For Composite
Side Top Rail:	Side Top Rail for Composite Trailer
Side Bottom Rail:	Side Bottom Rail for Composite (STD)
* Skylight-General Spec.:	Cluster Sky Light Lens on side wall for 24" or bigger post pitch (Single lens on two panels, next to each other, for 16" or less post pitches.)
* Skylight-Quantity:	Total 5. Both Side Wall Panel. (3) on Roadside and (2) on Curbside
* Skylight-Location:	Composite Both Side Wall Panel Location from Front, Specifically on panels #5, #9 on C/S & #3, #7, #11 on R/S
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

---

**REAR**

Rear Frame:	Swing Door, 2" Shallow Header (with 1 Lock Rod Per LH & RH Door)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
Door Type for Dry Van - SW:	0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
Option - Door & Hardware:	One(1) Rubber Door Bumper Standard (1" Deep) on Hinge of each Swing Door
Hinges:	Four (4) Aluminum Hinges per Door
* Additional Hinge Option:	Additional One(1) Aluminum Hinge (Total 5 Per Door)
* Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG) 30
Option - Horiz Member/Other:	Construction of two pieces standard stitch welding
Underide Bolt Spec.:	Zinc plated bolts & nuts - Standard
Dock Bumper:	Pair 3" X 6" Mold Bolted Bumper
Rubber Bumper Location:	Inboard of Light Protector Bars (Standard)

---

**LEFT GATE**

---

**ROOF**

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

---

**LINING/SCUFF**

Front Lining:	0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height
* Base Side Scuff:	6.5" High Integral Alum (Composite STD) with Additional scuff (Plastic, Corrugated or Wood)
* Additional Side Scuff:	18Ga x 6.5"H Corrugated Steel Butted to Intergral Aluminum

\* Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

**LANDING GEAR**

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG  
L/Gear Mt'g Method: Inboard Mounting (Standard)  
L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile  
L/Gear Ground Clearance: Nom. 12" Ground Clearance  
L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate  
L/Gear Crank Handle: Roadside  
L/Gear Options: None (HT STD)  
L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

**RUNNING GEAR**

Bogie Type: Sliding Tandem(2) Axle Bogie  
Axle Spacing: 49" Axle Spacing  
Axle ABS System: Tandem Axle w/2S1M ABS System  
Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear  
Option-Related Bogie Stopper Feature: STD plug stopper  
Susp. Manufacturer: Hendrickson  
Suspension Capacity: Standard Duty  
Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride  
Surelok (Anti-Dock): Surelok (Anti-Dock) Installed  
Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw  
Susp. Sub-Frame: Hendrickson K-2 STD Duty  
Type of Susp Spring: Air Bag  
Spring Specification: Air Bag  
Axle Supplier: Hendrickson  
Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)  
Axle-Track Length: 77-1/2"  
Axle-Spindle Type: Tapered Spindle  
Brake Lining Size: 16.5" X 7"  
Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)  
Brake Control System: 2S/1M Wabco ABS  
Spring Brake Control: Sealco 110500 Springbrake Priority  
Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)  
\* Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)  
\* Brake Chamber Spec.: Wabco Premium Chamber  
\* Stroke Length: 3" Long Stroke Length  
Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub  
Drum Specification: HT Standard (KIC) Cast Drum  
Hub/Drum-Opt(Nut&Other): Standard  
Bearing Specification: Stemco  
\* Lubrication Spec.: Chev Delo (Syn) Grease  
\* Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut  
\* Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)  
Tire Inflation Pressure: 100 PSI  
\* Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted over corner radius. (STD location)  
\* Tire Inflation Lamp Spec.: 33 Series Lamp

**ELECTRICAL**

Harness-General Spec.: Molded Color Code Phillips Harness with QCS Plug  
Harness-Special Feature: Manufacturer's Standard Feature  
Front Light: (2) Trucklite 33275Y LED PC Rated Mounted with Grommet  
\* Rear ID Header Light: (5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)  
\* Rear ID-Special Feature: Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop

functionality, 2 Lamps outboard with Marker & Turn functionality

Rear Side Marker Type(Shape): Mini Button Style Lamp

Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33275 w/ anti-theft hardware

Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD

S/T/Tail Light-Quantity & Type: (4) Trucklite 40 or 44 Series (Round Style) or Equivalent

S/T/Tail Light-Detail Spec: (4) Trucklite 44322R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets

Main Mid-Turn Light: Install the Mid turn lamp

Mid-Turn Mounting Method: Mounting Bracket

\* Main Mid-Turn Light-Detail Spec: (2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets

ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33275 w/ anti-theft hardware

ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD

License Light: (1) Trucklite 33010C LED

Option Related Harness/Wiring: Standard

Electrical Related Regulation: Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)

Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes

Decal Opt 2-Decal Location: Standard Application

Decal Opt 3-Decal Installation: Standard Application

Conspicuity Vendor: Avery

Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail

License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate

License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill

Furnish Document Holder: Factory Furnished

Document Holder Detail Spec: (1) Phillips 16-802

\* Document Holder/Manifest Loc.: Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

**PAIN/FINISH**

\* Upper Coupler Finish: Galvanized-Whole upper coupler section

\* Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)

\* Axle & Components Finish: Black Undercoating

\* Susp. Sub-Frame Finish: Black Undercoating

L/Gear(K-Bracing) Finish: Hot Dip Galvanized

\* L/Gear(Upper Leg) Finish: Hot Dip Galvanized

Rear Frame-Finish: Hot Dip Galvanized

Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)

Rear Underride-Finish & Spec.: Hot Dip Galvanized & Welded Horizontal Member

Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider: Factory Furnished Mudflaps

Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo

Mudflap Mounting Loc.: Suspension Frame

Mudflap Mounting: STD Location w/ H.D Washer Retainer

\* Lift Pad Spec.: Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.