

Hale Trailer Brake & Wheel 500012-500021



VTDE200SA2 (Model: VCAE200SAVT9E0402)		
XTP5390SA2 (Model: XCA5390SAXT859492) General		
SKU	XCA5390SAXT859492	
Capacity	80,000# Distributed - Self-Supporting, Properly Blocked	
	53 feet (Closed) to 90 feet (Open)	
Length Width	8 feet 6 inches	
width		
Gooseneck		
Kingpin 24 inches		
Loaded Fifth Wheel Height 49 inches		
Loaded Fifth Wheel Height		
Landing Gear	OEM Standard	
Bulkheads	None	
Bulkhead Pockets	4 - F-5 DOT-Type Steel	
Main Beams	Minimum Grade 80 Flanges	
Crossmembers	12 inch Centers - 4 in Jr I-Steel	
Deck Lock	Approx. Every 5 feet	
Front Corners	Tapered	
Side Rails	6 inch Structural Channel @ 6.5lbs/ft	
Stake Pockets	3/16 inch Steel on 24 inch Centers	
Pipe Spool	Single Pipe Spool	
Rubrail	2 1/2 inch x 3/8 inch Thick HD Mill Formed Steel	
Flooring	1 1/8 inch Wood	
Winch Track	Full-Length Steel on Roadside	
Sliding Winches	12 - without Straps	
Winch Straps	None	
Air and Electrical at Extension Locks	Inside Track System	
Toolbox	None	
Bumper	Meets Underride Requirements	
Mudflaps	1 Set - Fontaine	
VIN Plate	Bilingual VIN Plate	
Registration/Document Holder	Install Registration/Document Holder	
Rear Bridge: Axles		
Number of Axles	2	
Axle Spread	49 inches	
Brakes	Spring Brakes, Auto Slacks	
Dust Shield	None	
Hub and Drums	10-Hole Hub-Piloted with Outboard Cast Drums	
	Rear Bridge: Suspension	
Suspension	Hendrickson Air Ride on Slide Box - 60 inches Adjustable	
ABS	2S/1M - No Cable or Tool	
Manual Dump Valve	None	
Liquid Filled Gauge	None	
Load Scale	None	
	Wheels and Tires	
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-painted White	
Tires	11R 22.5 OEM Economical	
Hubodometer	None	
Inflation	None	
Wheel Ends	Grease in Hubs	
VVIICEI LIIU3	orease in mass	



Lighting	
Electrical System	Sealed Harness and LED Lights with 4 inch Flush Mounted Amber Strobes (No Battery Backup)
Tail Lights	3 Lights/Side, 3 Lights/Side on Rear
Paint	
Paint	Fontaine Black Polyurethane Enamel