

## Hale Trailer Brake & Wheel 500067-500071



**Detailed Specifications** 

Detailed Specifications	A CEPT HAVE TO A CEPT A
MAGNITUDE 55H FLD 26 (Model: MAG55H***F*826543)	
	General
SKU	MAG55H***F*826543
Capacity	55 Tons in 12-foot Length with 4 Axles Close Coupled or Single Axle Stinger - GAWR and Tire Ratings Determine Legal Loads
Load Base	12-foot Rigid 2-Point Load Centered in Deck Area with 4 Axles Close Coupled
Length (Trailer Only)	52 feet 0 inches
Width	8 feet 6 inches
Compatibility	Designed to Accept Optional 51/60 Rear Axle, Spreader, and/or 23 inch Flip Box
Weight	Est. Base Weight: 22634# +/- 3%
Gooseneck	
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11ft 11in overall Gooseneck Length) Set Up for Wetline Operation
Loaded Fifth Wheel Height	Dual Cam Pawl Arm Assembly with 7 Ride Height Positions (50 inches Nominal)
Kingpin	Dual Kingpin at 81 inch and 102 inch Radius
5	
Power Source	Set Up for Wet Line Operation
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
	Deck
Framework	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs
Deck Design	Flat Level Deck Design
Deck Length	26 feet 0 inches Clear Deck Length
Loaded Deck Height	22 inches with 6 inches Ground Clearance
Crossmembers	On 24 inch Centers (Nominal)
Flooring	2 inch Nominal Wood (Side Rails Only)
Front Ramps	None, Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats
Extension Brackets	12 pair - 24 Total Removable Swing Type, 2 Pair - 4 Total Heavy Duty Removable Hook-On Type
Toolbox	2 Fully Covered Trays in Front of Deck Between Mainbeams with Lockable Covers
Hammer Plate	None
Halliller Flate	
Rear Bridge: General	
Front Bogie Ramp	Sloped Steel Bogie Ramp (Full Width)
Boom Trough	V Crossmembers with Bolt-In V Pan
Deck to Bogie Connection	Fixed
Bolsters	Recessed
Covered Rear Bogie	None
Rear Bogie Height	40 7/8 inches to Top Flanges - 36 5/8 inches to Top of Bolsters
Connections for Future Axle Attachmer	nt Air and Electrical Connections to Go Along with Connecting Ears
Accent Package	None
Rear Bridge: Axles	
Number of Axles	3 Axles
Axle Capacity	25,000 lb. Nominal Capacity Per Axle NOTE: GAWR Determined by Suspension Type, Brakes, Tires and Other Components.
Axle Spread	54.5 inches (Between Axles)
Brakes	16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount
Spring Brakes	None
Dust Shield	None
Hubodometer	None
Trabodometer	
	Rear Bridge: Suspension
Suspension	Air Ride with Automatic Controls
ABS	None
Third Lift Axle	Air Lift Installed on Third Axle
Chain Lift	None
Ride Height Control	Dynamic Ride Height Adjustment (Whittle Valve)
Manual Dump Valve	Manual Dump Valve
Liquid Filled Gauge	None
Load Scale	None
Wheels and Tires	
Wheels	8.25 x 22.5 Steel Disc - Hub-Piloted
Tires	275/70R 22.5 H Ply OEM Standard
Inflation	None
IIIIacioii	Note:



**Detailed Specifications** 

Lighting		
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
Tail Lights	3 Tail Light Package	
Marker Lights	3 Marker Lights Per Side Including Mid-Turn	
Electrical Receptacle	J560 7-Pin Connector	
Paint		
Paint	Fontaine Black Polyurethane Enamel	
Miscellaneous		
Lash Rings	14 Pair - 28 Total	
Flag Holders	2 Pair Flag Holders	
Additional Options		
Flip Box	None	
Accent Package Installed on Flip Box	None	
Spreader	None	
Accent Package Installed on Rigid Spreader	None	
Flip Axle	None	
Dust Shields on Flip Axle	None	
Accent Package Installed on Flip Axle	None	

## MAGNITUDE 55H FLD 26



MAGNITUDE 55H FLD 26 Base Model (Note: Options not shown)



Sales Drawing: MAGNITUDE 55H FLD 26

