



Hale Trailer Brake & Wheel

500244-500255



XTP5390SA3 (Model: XCA5390SAXT859603)

General

SKU	XCA5390SAXT859603
Capacity	80,000# Distributed - Self-Supporting, Properly Blocked
Length	53 feet (Closed) to 90 feet (Open)
Width	8 feet 6 inches
Weight	Est. Configured Weight: 20300# +/- 3%

Gooseneck

Kingpin	24 inches
---------	-----------

Deck

Loaded Fifth Wheel Height	49 inches
Landing Gear	OEM Standard
Bulkheads	None
Bulkhead Pockets	4 - F-5 DOT-Type Steel
Main Beams	Minimum Grade 80 Flanges
Crossmembers	12 inch Centers - 4 in Jr I-Steel
Deck Lock	Approx. Every 5 feet
Front Corners	Tapered
Side Rails	6 inch Structural Channel @ 6.5lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
Pipe Spool	Single Pipe Spool
Rubrail	2 1/2 inch x 3/8 inch Thick HD Mill Formed Steel
Flooring	1 1/8 inch Wood
Winch Track	Full-Length Steel on Roadside
Sliding Winches	12 - without Straps
Winch Straps	None
Air and Electrical at Extension Locks	Inside Track System
Toolbox	None
Bumper	Meets Underride Requirements
Mudflaps	1 Set - Fontaine
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder

Rear Bridge: Axles

Number of Axles	3
Axle Spread	60 inches
Brakes	Spring Brakes, Auto Slacks
Dust Shield	None
Hub and Drums	10-Hole Hub-Piloted with Outboard Cast Drums

Rear Bridge: Suspension

Suspension	Hendrickson Air Ride on Slide Box - 60 inches Adjustable
ABS	2S/1M - No Cable or Tool
Manual Dump Valve	None
Liquid Filled Gauge	None
Load Scale	None

Detailed Specifications

Wheels and Tires	
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-painted White
Tires	11R 22.5 OEM Economical
Hubodometer	None
Inflation	None
Wheel Ends	Grease in Hubs
Lighting	
Electrical System	Sealed Harness and LED Lights with 4 inch Flush Mounted Amber Strobes (No Battery Backup)
Tail Lights	3 Lights/Side, 3 Lights/Side on Rear
Paint	
Paint	Fontaine Black Polyurethane Enamel
Terms	
Please Note	Price Includes Commodity Surcharges
Commercial Terms	Ex Works- Springville, AL, USA
XTP5390SA3	



[XTP5390SA3 Base Model](#) (Note: Options not shown)

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

