



Hale Trailer Brake & Wheel

534537-534543

Infinity Flat 48' Sliding Air Tandem (Model: HCICF12SAT)	
	Est. Wt.: 10,673# +/- 3%
Length / Width: 48 feet x 102 inches	
Suspension Type: Sliding air tandem	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Single Coil Hauling Package: Included	
Side Rails: Exclusive Routed Aluminum (RASR) designed for strength and impact	
Chain Cargo Tie Downs: 15 pair recessed in siderails	
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
Rubrail: Integrated with siderail	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkheads: None standard	
Bulkhead Pockets: None standard	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 49 inches	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 295/75R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Spare Tire Carrier: None standard	
Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider; 60" adjustable	
Air Assist Slide Box Pins: Standard mount of controls on slider frame	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: Not applicable	
Front Corners: Tapered steel	
Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD	
Paint: Black urethane on steel parts with Infinity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Weld-on type - meets underdrive requirements - painted steel	
Mudflaps: 1 set OEM standard	
Winch Track: Full length integrated double L type aluminum on both sides - STANDARD	
Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD	
Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: None standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.