



## Hale Trailer Brake & Wheel

534738 - 534757

| Infinity Flat 48' Sliding Air Tandem (Model: HCICF12SAT)  |                          |
|---|--------------------------|
|   | Est. Wt.: 10,680# +/- 3% |
| <b>Length / Width:</b> 48 feet x 102 inches   |                          |
| <b>Suspension Type:</b> Sliding air tandem  |                          |
| <b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads                |                          |
| <b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips  |                          |
| <b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel   |                          |
| <b>Single Coil Hauling Package:</b> Included  |                          |
| <b>Side Rails:</b> Exclusive Routed Aluminum (RASR) designed for strength and impact                        |                          |
| <b>Chain Cargo Tie Downs:</b> None included   |                          |
| <b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets) |                          |
| <b>Rubrail:</b> Integrated with siderail  |                          |
| <b>Main Beams:</b> 130K load bearing flanges  |                          |
| <b>Kingpin:</b> 30 inches   |                          |
| <b>Loaded Fifth Wheel Height:</b> 49 inches   |                          |
| <b>Landing Gear:</b> OEM Standard   |                          |
| <b>Knee Braces:</b> Fabricated on approx. 60 inch C/C   |                          |
| <b>Bulkheads:</b> None standard   |                          |
| <b>Bulkhead Pockets:</b> 4 bulkhead pockets only -welded to front   |                          |
| <b>Number of Axles:</b> 2   |                          |
| <b>Axle Spindle:</b> Tapered  |                          |
| <b>Brakes:</b> Spring brakes, auto slacks   |                          |
| <b>Air Line Filters:</b> (2) Meritor In-line type installed   |                          |
| <b>ABS:</b> 4S/2M - no cable or tool  |                          |
| <b>Axle Spread:</b> 49 inches   |                          |
| <b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums  |                          |
| <b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***                                       |                          |
| <b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD                                 |                          |
| <b>Tires:</b> 11R 22.5 14PR OEM standard with lower rolling resistance                                      |                          |
| <b>Tire Inflation System:</b> None installed  |                          |
| <b>Spare Tire Carrier:</b> None standard  |                          |
| <b>Suspension Detail:</b> Hendrickson AAZNT46K Intraax air ride slider; 60" adjustable                      |                          |
| <b>Air Assist Slide Pins:</b> Standard mount of controls on slider frame                                    |                          |
| <b>Auto Glad Hand Dump:</b> Installed   |                          |
| <b>Electric Dump Valve:</b> Not applicable  |                          |
| <b>Front Corners:</b> Tapered steel   |                          |
| <b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear - STANDARD                              |                          |
| <b>Paint:</b> Black urethane on steel parts with Infinity decals - STANDARD                                 |                          |
| <b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails                                  |                          |
| <b>Bumper:</b> Weld-on type - meets underride requirements - painted steel                                  |                          |
| <b>Mudflaps:</b> 1 set OEM standard   |                          |
| <b>Winch Track:</b> Full length integrated double L type aluminum on both sides - STANDARD                  |                          |
| <b>Sliding Winches:</b> 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD           |                          |
| <b>Winch Straps:</b> None standard  |                          |
| <b>Dock Bumpers:</b> 1 pair rubber on rear  |                          |
| <b>Hubodometer:</b> None standard   |                          |
| <b>Registration Holder:</b> Install registration holder - OEM standard                                      |                          |
| <b>Tool Box:</b> None standard  |                          |
| <b>VIN Plate:</b> Bilingual US/Canadian VIN plate   |                          |

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.