



## Hale Trailer Brake & Wheel

### 537092 - 537100

**Velocity Drop Deck 48' Closed Spring (Model: HAVSD12CTS)**

<b>Length / Width:</b> 48 feet x 102 inches	
<b>Suspension Type:</b> Spring tandem	
<b>Deck Lengths:</b> 10 feet front and 38 feet rear	
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
<b>Rear Deck Height:</b> 40 inches - loaded	
<b>Flooring:</b> 1 1/8 inch Apitong wood	
<b>Crossmembers:</b> 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers	
<b>Pipe Spools:</b> Double between stake pockets	
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel	
<b>Main Beams:</b> 130K load bearing flanges	
<b>Kingpin:</b> 18 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkheads:</b> None standard	
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 49 inches - set at rear	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Oil in hubs	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
<b>Tires:</b> 255/70R 22.5 16PR OEM standard	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> Hutch H-9700 3-leaf spring	
<b>Front Corners:</b> Tapered	
<b>Electrical System: LED:</b> 3 lights/side, 2 lights/side on rear- STANDARD	
<b>Paint:</b> Black urethane with Velocity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements	
<b>Mudflaps:</b> 1 set OEM standard	
<b>Winch Track:</b> Steel on road side: 8-foot front deck and full length on rear deck where possible	
<b>Sliding Winches:</b> 12 standard: 2 front deck and 10 rear deck	
<b>27' Winch Straps:</b> None standard	
<b>30' Winch Straps:</b> None standard	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Spare Tire Carrier:</b> 1 standard - mounted between lower gooseneck beams	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> Install registration holder - OEM standard	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.