



Hale Trailer Brake & Wheel
540342-540353



Revolution 52 Alum Flat 48' Wide Spread Air (Model: HCR5212WSA)	
Length / Width: 48 feet x 102 inches	
Suspension Type: Wide spread air	
Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads	
Flooring: Knurled extruded 3-1/8 aluminum, StirLITE Friction Stir Welded Floor with 2 Apatong wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear	
Side Rails: Exclusive Revolutionary RASR Rail Technology – one piece routed aluminum designed for strength and impact	
Stationary Chain Cargo Tie Downs: 15 pair - recessed in siderails	
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)	
Rubrail: Integrated with side rail	
Main Beams: Extruded aluminum - 8.25 inch flange	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: Jost AX100G19 ALUMILIGHT Aluminum Landing Gear with forward & rear bracing	
Bulkheads: None standard	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks, Aluminum air tank	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 122 inches - set at rear	
Hub and Drums: 10-hole hub-piloted with outboard cast drums - STANDARD	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 aluminum LVL One buffed wheels	
Tires: 11R 22.5 14PR economical OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: AANT23K Intraax air ride - Galvanized Hangers & Bracing	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle	
Air Lift: None standard	
Front Corners: Tapered	
Electrical System: Exclusive Revolution Technology: LED: 5 lights/side, 3 rear recessed light bars, with 10 Year Comprehensive Electrical System Warranty	
Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections	
Paint: Black urethane on steel parts with Revolution decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Meets U.S. underride requirements	
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle	
Spare Tire Carrier: None standard	
Winch Track: Dual full-length integrated aluminum – double L design	
Sliding Winches: 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD	
27' Winch Straps: None standard	
30' Winch Straps: None standard	
Sliding J-Hook for Ring vs. Flat Hook on 4" Strap: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Install registration holder - OEM standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.