



Hale Trailer Brake & Wheel

540408-540431



Velocity 48' Spring Slider (Model: HAVSF12SST)

Length / Width: 48 feet x 102 inches	
Suspension Type: Sliding spring tandem	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch Apitong wood	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Pipe Spools: Double between stake pockets	
Rubrail: 3/8 inch x 2 1/2 inch steel	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkheads: Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 49 inches	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Oil in hubs	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 11R22.5 14PR OEM STANDARD	
Tire Inflation System: None standard	
Suspension Detail: Hutch H-9700 3-leaf spring slider - 60 inches adjustable	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 2 lights/side on rear- STANDARD	
Paint: Black urethane with Velocity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed on rubrails	
Bumper: Weld-on type - meets underride requirements	
Mudflaps: 1 set OEM standard	
Spare Tire Carrier: None standard	
Winch Track: Steel on road side	
Sliding Winches: 12 standard	
27' Winch Straps: None standard	
30' Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Installed OEM Standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.