



Hale Trailer Brake & Wheel

540646-540651



Infinity Drop Deck 53' Rear Axle Slide (Model: HAICD22RSA)

Length / Width: 53 feet x 102 inches	
Suspension Type: Rear axle slide	
Deck Lengths: 11 feet front and 42 feet rear	
Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads	
Rear Deck Height: 40 inches - loaded	
Flooring: 1 1/8 inch aluminum with 4 Apitong wood nailer strips	
Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
Single Coil Hauling Package: Included	
Side Rails: Exclusive Revolutionary RASR Rail Technology – one piece routed aluminum designed for strength and impact	
Chain Cargo Tie Downs: 17 pair recessed in siderails	
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
Rubrail: Integrated with siderail	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets & Bulkhead: None standard	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 122 inches open - 61 inches closed: California legal and meets Canadian RTAC and BC dimensional specifications in closed position	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 255/70R 22.5 16PR OEM standard	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson AANL23K and AAZL23K buttoned-up Intraax air ride axles	
Air Assist Slide Box Pins: Standard mount of controls on slider frame	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD	
Paint: Black urethane on steel parts with Infinity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Weld-on type - meets underride requirements - painted steel	
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle	
Winch Track: Full length integrated double L type aluminum on both sides where possible - STANDARD	
Sliding Winches: 12 total, 2 front deck and 10 rear deck: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers – STANDARD	
27' Winch Straps: None standard	
30' Winch Straps: None standard	
Dock Bumpers: 1 pair rubber on rear	
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams at drop	
Hubodometer: None standard	
Registration Holder: None standard	
Tool Box: 1 aluminum double door box - 18 inches x 18 inches x 60 inches - installed Road Side	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.