



Hale Trailer Brake & Wheel

540670-540681



Revolution 52 Alum Flat 48' Wide Spread Air (Model: HCR5212WSA)

Length / Width: 48 feet x 102 inches
Suspension Type: Wide spread air
Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Flooring: Knurled extruded 3-1/8 aluminum, StirLITE Friction Stir Welded Floor with 2 Apitong wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear
Side Rails: Exclusive Revolutionary RASR Rail Technology – one piece routed aluminum designed for strength and impact
Stationary Chain Cargo Tie Downs: 15 pair - recessed in siderails
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)
Rubrail: Integrated with side rail
Main Beams: Extruded aluminum - 8.25 inch flange
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: Jost AX100G19 ALUMILIGHT Aluminum Landing Gear with forward & rear bracing
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks, Aluminum air tank
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Axle Spread: 122 inches - set at rear
Hub and Drums: 10-hole hub-piloted with outboard cast drums - STANDARD
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 aluminum LVL One buffed wheels
Tires: 275/80R 22.5 14PR Michelin XTE
Tire Inflation System: Hendrickson TIREMAAX PRO
Suspension Detail: Hendrickson AANT23K Intraax air ride
Auto Glad Hand Dump: Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Air Lift: None standard
Front Corners: Tapered
Electrical System: Exclusive Revolution Technology: LED: 5 lights/side, 3 rear recessed light bars, with 10 Year Comprehensive Electrical System Warranty
Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections
Paint: Black urethane on steel parts with Revolution decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Meets U.S. underride requirements
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle
Spare Tire Carrier: None standard
Winch Track: Dual full-length integrated aluminum – double L design
Sliding Winches: 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD
27' Winch Straps: None standard
30' Winch Straps: None standard
Sliding J-Hook for Ring vs. Flat Hook on 4" Strap: None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: None standard
Tool Box: 2 aluminum double door boxes - 24 inches x 24 inches x 60 inches - installed one ea. side; includes 8 sliding securement devices and 8 chocks
VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.