



# Hale Trailer Brake & Wheel

## 542813-542857

### Infinity Flat 48' Air Slider (Model: HAICF12SAT)

<b>Length / Width:</b> 48 feet x 102 inches	
<b>Suspension Type:</b> Sliding air tandem	
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
<b>Flooring:</b> 1 1/8 inch aluminum with 4 Apitong wood nailer strips	
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel	
<b>Single Coil Hauling Package:</b> <b>Included</b>	
<b>Side Rails:</b> Exclusive <b>Revolutionary RASR Rail Technology</b> - one piece routed aluminum designed for strength and impact	
<b>Chain Cargo Tie Downs:</b> <b>15 pair recessed in siderails</b>	
<b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
<b>Rubrail:</b> Integrated with siderail	
<b>Main Beams:</b> 130K load bearing flanges	
<b>Kingpin:</b> 30 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkhead Pockets &amp; Bulkhead:</b> <b>4 DOT type bulkhead pockets only - welded to front</b>	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 49 inches	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
<b>Tires:</b> <b>11R 22.5 14PR OEM standard tires</b>	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable	
<b>Air Assist Slide Box Pins:</b> Standard mount of controls on slider frame	
<b>Auto Glad Hand Dump:</b> Installed	
<b>Front Corners:</b> Tapered steel	
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear - STANDARD	
<b>Paint:</b> Black urethane on steel parts with Infinity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements - painted steel	
<b>Mudflaps:</b> 1 set OEM standard	
<b>Spare Tire Carrier:</b> None standard	
<b>Winch Track:</b> Full length integrated double L type aluminum on both sides - STANDARD	
<b>Sliding Winches:</b> 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD	
<b>27' Winch Straps:</b> None standard	
<b>30' Winch Straps:</b> <b>(12) 30 feet x 4 inches installed</b>	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> <b>Install registration holder - OEM standard</b>	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.