



Hale Trailer Brake & Wheel

542858-542872



Infinity Flat 48' Wide Spread Air (Model: HAICF12WSA)

Length / Width: 48 feet x 102 inches	
Suspension Type: Wide spread air	
Frame Rating: 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch aluminum with 4 Apitong wood nailer strips	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Single Coil Hauling Package: Included	
Side Rails: Exclusive Revolutionary RASR Rail Technology - one piece routed aluminum designed for strength and impact	
Chain Cargo Tie Downs: 15 pair recessed in siderails	
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
Rubrail: Integrated with siderail	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets & Bulkhead: None standard	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 122 inches - set at rear	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 11R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson AANT23K Intraax air ride	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle	
Air Lift: None standard	
Front Corners: Tapered steel	
Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD	
Paint: Black urethane on steel parts with Infinity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Weld-on type - meets underride requirements - painted steel	
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle	
Spare Tire Carrier: None standard	
Winch Track: Full length integrated double L type aluminum on both sides - STANDARD	
Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD	
27' Winch Straps: None standard	
30' Winch Straps: (12) 30 feet x 4 inches installed	
Dock Bumpers: 1 pair rubber on rear	
Hubodometer: None standard	
Registration Holder: Install registration holder - OEM standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.