



Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

Hale Trailer Brake & Wheel 544968-544974

| Velocity Drop Deck 48' Closed Air (Model: HAVSD12CTA) | |
|--|--|
| velocity brop beck 48 Closed All (Model: HAVSD12CTA) | |
| Length / Width: 48 feet x 102 inches | |
| Suspension Type: Air tandem | |
| Deck Lengths: 10 feet front and 38 feet rear | |
| Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads | |
| Rear Deck Height: 40 inches - loaded | |
| Flooring: 1 1/8 inch Apitong wood | |
| Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel | |
| Side Rails: 6 inch structural channel @ 6.5 lbs/ft | |
| Stake Pockets: 3/16 inch steel on 24 inch centers | |
| Pipe Spools: Double between stake pockets | |
| Rubrail: 3/8 inch x 2 1/2 inch steel | |
| Main Beams: 130K load bearing flanges | |
| Kingpin: 18 inches | |
| Loaded Fifth Wheel Height: 49 inches | |
| Landing Gear: OEM standard | |
| Knee Braces: Fabricated on approx. 60 inch C/C | |
| Bulkheads: None Standard | |
| Bulkhead Pockets: 4 - F-5 DOT-type steel | |
| Number of Axles: 2 | |
| Axle Spindle: Tapered | |
| Brakes: Spring brakes, auto slacks | |
| Air Line Filters: (2) Meritor In-line type installed | |
| ABS: 4S/2M - no cable or tool | |
| Axle Spread: 49 inches - set at rear | |
| Hub and Drums: 10-hole hub-piloted with outboard cast drums | |
| Wheel Ends: Grease in hubs - *** 5-year wheel end warranty *** | |
| Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD | |
| Tires: 255/70R 22.5 16PR OEM Standard | |
| Tire Inflation System: None standard | |
| Suspension Detail: AANL23K Intraax air ride | |
| Auto Glad Hand Dump: Installed | |
| Front Corners: Tapered | |
| Electrical System: LED: 3 lights/side, 2 lights/side on rear- STANDARD | |
| Paint: Black urethane with Velocity decals - STANDARD | |
| Conspicuity Tape: Per NHTSA specs - installed on rubrails | |
| Bumper: Weld-on type - meets underride requirements | |
| Mudflaps: 1 set OEM standard | |
| Winch Track: Steel on road side: 8-foot front deck and full length on rear deck where possible | |
| Sliding Winches: 12 standard: 2 front deck and 10 rear deck | |
| 27' Winch Straps: None standard | |
| 30' Winch Straps: None standard | |
| Dock Bumpers: 1 pair rubber on rear | |
| Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams | |
| Hubodometer: None standard Posistration Holdon, Install registration holdon - OEM standard | |
| Registration Holder: Install registration holder - OEM standard | |