



Hale Trailer Brake & Wheel

545105-545106

Infinity Forklift Flat 48' Air Ride (Model: HCICF12CTA)

| | |
|--|--|
| Length / Width: 48 feet x 102 inches | |
| Suspension Type: Closed Tandem Air Ride Fixed position due to Forklift kit installation | |
| Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads | |
| Flooring: 1 1/8 inch aluminum with 4 Apitong wood nailer strips | |
| Crossmembers: 12 inch centers - 4 inch jr. I-steel | |
| Single Coil Hauling Package: Included | |
| Side Rails: Exclusive Revolutionary RASR Rail Technology - one piece routed aluminum designed for strength and impact | |
| Chain Cargo Tie Downs: None included | |
| Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets) | |
| Rubrail: Integrated with siderail | |
| Main Beams: 130K load bearing flanges | |
| Kingpin: 30 inches | |
| Loaded Fifth Wheel Height: 49 inches | |
| Landing Gear: Jost A400G19 2-speed with roadside crank & cushion foot | |
| Knee Braces: Fabricated on approx. 60 inch C/C | |
| Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front | |
| Bulkhead: Removeable steel 4 post DOT bulkhead - no turnback - 48" high with front pockets | |
| Number of Axles: 2 | |
| Axle Spindle: Tapered | |
| Brakes: Spring brakes, auto slacks | |
| Air Line Filters: (2) Meritor In-line type installed | |
| ABS: 4S/2M - no cable or tool | |
| Axle Spread: 49 inches | |
| Hub and Drums: 10-hole hub-piloted with outboard cast drums | |
| Wheel Ends: Grease in hubs - *** 5-year wheel end warranty *** | |
| Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD | |
| Tires: 295/75R 22.5 14PR OEM standard tires | |
| Tire Inflation System: None standard | |
| Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider - FIXED | |
| Air Assist Slide Box Pins: None | |
| Auto Glad Hand Dump: Installed | |
| Front Corners: Tapered steel | |
| Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD | |
| Paint: Black urethane on steel parts with Infinity decals - STANDARD | |
| Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails | |
| Bumper: Weld-on type - meets underride requirements - painted steel; Uprights notched inside for additional fork clearance | |
| Mudflaps: 1 set OEM standard | |
| Spare Tire Carrier: None standard | |
| Winch Track: Full length integrated double L type aluminum on both sides - STANDARD | |
| Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers - STANDARD | |
| 27' Winch Straps: None standard | |
| 30' Winch Straps: | |
| Dock Bumpers: Not Applicable* | |
| Hubodometer: None standard | |
| Registration Holder: OEM standard installed | |
| Tool Box: None standard | |
| VIN Plate: Bilingual US/Canadian VIN plate | |
| Rear Forklift Kit: Factory installed Fontaine Updated Design "Universal Type" kit with adjustable curved upper wheel stops and removable lower Moffet Tire Supports each side; Dealer and Customer are responsible for final adjustment to stops and kit in order to fit actual lift being transported. | |
| Counterweights: Combined Approximate Weight of 1,112#: (1) Steel mounted at front center- Approx. 610#; (2) Steel: One ea. side mounted at front corners- Approx. combined weight of 502# | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.