



**Fontaine 48' Infinity Drop Deck  
Wide Spread Air  
HCICD12WSA  
568732 - 568751**

<b>Infinity Drop Deck 48' Wide Spread Air (Model: HCICD12WSA)</b>	
<b>Length / Width:</b> 48 feet x 102 inches	
<b>Suspension Type:</b> Wide Spread Air	
<b>Deck Lengths:</b> 10 feet front and 38 feet rear	
<b>Frame Rating:</b> 80,000 lbs. distributed-55,000 lbs concentrated in 4 feet	
<b>Rear Deck Height:</b> 40 inches - loaded	
<b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips; NOTE: Nailer strips to br left off of rear deck only and shipped loose.	
<b>Crossmembers:</b> 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel	
<b>Single Coil Hauling Package:</b> Included	
<b>Side Rails:</b> Exclusive routed aluminum (RASR) designed for strength and impact	
<b>Chain Cargo Tie Downs:</b> None Standard	
<b>Stake Pockets:</b> Routed Aluminum on 24 inch centers (2 Load securement openings between stake pockets)	
<b>Rubrail:</b> Integrated with siderail	
<b>Main Beams:</b> Minimum grade 130 flanges	
<b>Kingpin:</b> 18 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkheads:</b> None Standard	
<b>Bulkhead Pockets:</b> None Standard	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 122 inches - set at rear	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
<b>Tires:</b> 255/70R 22.5 16PR OEM standard	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> AANL23K Intraax air ride	
<b>Auto Glad Hand Dump:</b> Installed	
<b>Electric Dump Valve:</b> Wired to 7 way auxiliary socket to dump rear axle	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear- STANDARD	
<b>Paint:</b> Black urethane on steel parts with Infinity decals	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements - painted steel	
<b>Mudflaps:</b> 2 sets OEM standard	
<b>Winch Track:</b> Full length integrated double L type auminum on both sides where possible	
<b>Sliding Winches:</b> Not Included	
<b>Winch Straps:</b> None standard	
<b>Dock Bumpers:</b> 1 pair rubber on each	
<b>Spare Tire Carrier:</b> 1 standard - mounted between lower gooseneck beams at drop	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> None standard	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Standard US VIN plate	Est. Wt.: 10,204#

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.