



Hale Trailer Brake & Wheel
576051 - 576065

Xcalibur Extendable 53ft - 90ft Air Ride Slider Tridem (Model: XTP5390SA3)	
	Est. Wt. (with selected options): 20260# +/- 3%
Length / Width: 53 feet to 90 feet - adjustable with locks approx. every 5 feet - 102 inches wide	
Suspension: Sliding air tridem	
Frame Rating: 80,000 lbs distributed - self-supporting, properly blocked	
Flooring: 1 1/8 inch wood	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Rubrail: 2 1/2 inch x 3/8 inch thick HD mill formed steel	
Main Beams: Minimum grade 80 flanges	
Air and Electrical @ Extension Locks: Inside track system	
Kingpin: 24 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard	
Bulkheads: None	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
Number of Axles: 3	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Dust Shields: None	
ABS: 4S/2M - no cable or tool	
Axle Spread: 60 inches	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white -	
Tires: 11R 22.5	
Suspension: Hendrickson air ride on slide box - 60 inches adjustable	
Front Corners: Tapered	
Electrical System: Sealed harness and LED Lights: 3 lights/side, 2 lights/side on rear	
Paint: Black urethane	
Conspicuity Tape: Per NHTSA specs - installed on rub rail	
Bumper: Meets override requirements	
Mudflaps: 1 set Fontaine	
Winch Track: Full-length steel on road side	
Sliding Winches: 12 - without straps	
Winch Straps: None	
Hubodometer: None	
Registration/Document Holder: Install registration/document holder	
Tool Box: None	
VIN Plate: US VIN plate	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.