

HALE TRAILER BRAKE & WHEEL



Hale Trailer Brake & Wheel 576104 - 576107

Renegade LX40 18 Air Tandem (Model: RENEGADELX40)	
	Est. Wt.: 16140# +/- 3%
Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Compatibility: Designed to accept third flip axle	
Length / Width: 47 feet 11 inches - 102 inches wide	
Gooseneck Design: Mechanical removable with removable fifth wheel guide rollers - Combination figure-8 plate which provides 50 inches and 52 inches loaded - Swing radius of 81 inches	
Gooseneck Platform: Full-width gooseneck platform with 1 1/8 inch wood floor	
Tool Box: None	
Gooseneck Fenders: Aluminum fenders at rear of gooseneck	
Electrical Receptacle: J560 7-pin connector	
Deck Design: Flat level deck design	
Deck Length: 29 feet 0 inches clear deck length	
Loaded Deck Height: 18 inches with 6 inches ground clearance	
Crossmembers: On 12 inch centers	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: None	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Mini Boom Trough & Traction Cleats: None	
Deck to Bogie Connection: Fixed	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes: Spring brakes (2 axles)	
Dust Shields: None	
Suspension: Air ride with automatic controls	
Tires: 255/70R 22.5 H ply OEM Standard	
Wheels: 8.25 x 22.5 steel disc - hub-piloted	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 40 inches	
Bumper: 3 tail light package	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Width: 8 feet 6 inches	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Flip Axle: None	
Dust Shields on Flip Axle: None	
Paint: Fontaine black polyurethane enamel	
Lash Rings: 9 pair - 18 total	

Flag Holders: 2 pair flag holders	
ABS: 4S/2M system without diagnostic tool and cable	
Liquid Filled Gauge: Included	
Marker Lights: 7 marker lights per side including mid-turn	
Accent Package: Stainless steel bumper insert	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.