

HALE TRAILER BRAKE & WHEEL



Hale Trailer Brake & Wheel 576505-576508

| Magnitude 55L 26 Air Tridem (Flat Low Deck) (Model: MAG55LCC) | |
|--|-------------------------|
| | Est. Wt.: 22760# +/- 3% |
| Capacity: 55 tons in 13-foot length with 4 axles close coupled; - GAWR and tire ratings determine legal payloads | |
| Load Base: 13-foot rigid 2-point load centered in deck area with 4 axles close coupled | |
| Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs | |
| Compatibility: Designed to accept 55/60 rear axle below | |
| Gooseneck Design: Hydraulic removable non-ground bearing design | |
| Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal) | |
| Swing Radius: 108 inches (12 feet 7 inches overall gooseneck length) | |
| Kingpin: Removable kingpin at 108 inch radius | |
| Alternate Kingpin: Alternate Kinpin location at 96 inch radius | |
| Power Source: Set up for wet line operation | |
| Electrical Receptacle: J560 7-pin connector | |
| Deck Width: 8 feet 6 inches overall (unless optional deck width is selected) | |
| Deck Length: Flat Level Deck (FLD) design - standard 26 feet clear deck length | |
| Loaded Deck Height: 18 inches with 6 inches ground clearance | |
| Flooring: 2 inch nominal wood - side rails only | |
| Front Ramps: Manual front approach ramps included | |
| Front Bogie Ramp: Included as standard | |
| Extension Brackets: 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck) | |
| Deck to Bogie Connection: Fixed | |
| Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers. | |
| Crossmembers: Recess last 3 crossmembers in deck | |
| Hammer Plate: Hammer Plate (16in x 60in x 1/2 in) installed over recessed crossmembers. Preforated plate under hammer plate | |
| Number of Axles: 3 axles | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 54.5 inches (between axles) | |
| Dust Shields: None | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Suspension: Air ride | |
| First Axle Lift: None | |
| Third Axle Lift: Air lift | |
| Tires: 275/70R 22.5 OEM standard | |
| Wheels: 8.25 x 22.5 steel disc - hub-piloted | |
| Bolsters: Recessed load bearing between all axles and rear of last axle | |
| Covered Rear Bogie: None | |
| Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters | |
| Boom Trough: V-style boom trough with bolt-in V pan | |
| Mechanical Ride Height Control: Mechanical ride height control valve (Whittle Style) | |
| Manual Dump Valve: Installed | |
| Bumper: Heavy duty V-style rear bumper | |
| Width: 8 feet 6 inches | |

| | |
|--|--|
| Flip Axle: None standard | |
| Dust Shields on Flip Axle: None standard | |
| Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes | |
| Paint: Fontaine standard black polyurethane enamel | |
| Lash Rings: 19 pair - 38 total | |
| Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper | |
| Accent Package: None | |
| Liquid Filled Gauge: None | |
| VIN Plate: Bilingual VIN plate | |
| Registration/Document Holder: Install registration/document holder | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.